


| | | REVISIONS | | | |
|-----|--------|------------------------|---------|-------|-------|
| REV | ECO | DESCRIPTION | DATE | BY | APPR |
| A3 | - | RELEASE NEW DWG FORMAT | 12DEC13 | DRP | |
| A4 | C0540S | UPDATE DIMENSIONS | 23JUN16 | JONY | TOMMY |
| A5 | - | ADD COLOR OPTION | 23NOV20 | LOUIE | TOMMY |


PLUG, 2 SOCKET, AT SERIES, REDUCED DIA. WIRE SEAL


AT06-2S-RD01XXX

3

ΞΞ








NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: REDUCED DIAMETER WIRE SEAL
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 13 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE:
 - IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)
 - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.7 RoHS COMPLIANT
- 4. MATING PART: AT04-2P* RECEPTACLE (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

| 6 | 6 CONTACT SIZE AND REAR SEAL WIRE RANGE: | | | | | | | |
|---|--|----------------------|----------------------|-----------------------------|--|--|--|--|
| | CONTACT SIZE | MIN. INSUL O.D. | MAX. INSUL O.D. | TYPICAL WIRE RANGE | | | | |
| | 16 | 1.35 mm (.053 in) | 3.05 mm (.120 in) | 14 - 20 AWG (2.0-0.5mm²) | | | | |



| PART NUMBER CHART | | | | |
|-------------------|-----------------|--|--|--|
| COLOR | PART NUMBER | | | |
| GREY | AT06-2S-RD01 | | | |
| BLACK | AT06-2S-RD01BLK | | | |
| BLUE | AT06-2S-RD01BLU | | | |
| BROWN | AT06-2S-RD01BRN | | | |
| GREEN | AT06-2S-RD01GRN | | | |
| RED | AT06-2S-RD01RED | | | |
| WHITE | AT06-2S-RD01WHT | | | |
| YELLOW | AT06-2S-RD01YEL | | | |
| ORANGE | AT06-2S-RD01ORG | | | |

STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLORS SHOWN IN PART NUMBER CHART ARE AVAILABLE VIA SPECIAL ORDER.

| | SEE PART N | UMBER CHART | | REF: DT06-2S-C015, DT06-2S-CE06 | | | | |
|--|-------------------------------|--|---|------------------------------------|--------------------------------------|-----------------|----------------|------|
| | PART N | T NUMBER | | | DESCRIPTION | | | ITEM |
| QUANTITY | | Г | MAT | ERI | ALS LI | ST | | • |
| UNLESS OTHER | | SIGN | ATURES | DATE | | mnha | SOOL | |
| All dimensions are in metric(mm). Tolerances are as follows: | | DRAWN: | LOUIE | 23NOV20 | | mphe | | |
| 1 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08 | Fractions ±1/64 Angles ±1° | CHECKED: | ORION | 25NOV20 | Sine Systems - www.amphenol-sine.com | | | |
| 3) Note reference | - /x | ENGINEER: | | | 44724 Morley Drive | | | |
| MATERIAL SPECIFICA | TIONS: | APPROVAL: | TOMMY | 27NOV20 Clinton Township, MI 48036 | | 3036 | | |
| | | CUSTOMER: | | | PLI | JG, 2 SOCKET, A | Γ SERIES, | |
| | | THIS DRAWING | | | REDI | JCED DIAMETER | WIRE SEAL | |
| PROCESS SPECIFICATIONS: SPECIFICATIONS AND SHOWN HEREON ARE THE AMPHENOL COR OF REPRODUCTION A DIMENSIONS ARE SUE | | NS AND PERFO ON ARE THE PE OL CORPORATION OTION ARE IMP | RMANCE DATA ROPERTY OF ON. NO RIGHTS LIED. ALL | B C- | AT06-2S-RI | | REVISION A5 | |
| | | MANUFACTUR | | | | SHEET 1 OF | 1 | |

A Series™ - Contact Size 16 Options (Works with: AT, ATV, AHD-9, ARC, DuraMate and PanelMate Series)

| | Machined Contacts, Sockets & Pins | | | | | |
|-------------------|--|------|-------|----------|--|--|
| Part Number | Description | Size | AWG | Туре | | |
| AT60-215-1631 | Male Contact - Pin, Gold-plated | 16 | 14 | Machined | | |
| AT62-209-1631 | Female Contact - Socket, Gold-plated | 16 | 14 | Machined | | |
| AT60-215-16141 | Male Contact - Pin, Nickel-plated | 16 | 14 | Machined | | |
| AT62-209-16141 | Female Contact - Socket, Nickel-plated | 16 | 14 | Machined | | |
| AT60-202-1631 | Male Contact - Pin, Gold-plated | 16 | 16-20 | Machined | | |
| AT62-201-1631 | Female Contact - Socket, Gold-plated | 16 | 16-20 | Machined | | |
| AT60-202-16141 | Male Contact - Pin, Nickel-plated | 16 | 16-20 | Machined | | |
| AT62-201-16141 | Female Contact - Socket, Nickel-plated | 16 | 16-20 | Machined | | |
| AT60-202-1631-22 | Male Contact - Pin, Gold-plated | 16 | 22-24 | Machined | | |
| AT62-201-1631-22 | Female Contact - Socket, Gold-plated | 16 | 22-24 | Machined | | |
| AT60-202-16141-22 | Male Contact - Pin, Nickel-plated | 16 | 22-24 | Machined | | |
| AT62-201-16141-22 | Female Contact - Socket, Nickel-plated | 16 | 22-24 | Machined | | |

| Tooling - Machined Contacts | | | | |
|-----------------------------|---|--|--|--|
| Part Number | Description | | | |
| AUTK-16 | Hand Crimp Tool, Size 16 | | | |
| AUTK-100 | Universal Heavy Duty Contact Crimping Tool Kit, Size 12/16/20 | | | |
| CA-5D12 | Universal Hand Crimp Tool, Size 12/16/20 | | | |
| CA-5E12 | Pneumatic Crimp Tool, Size 12/16/20 | | | |

| Contact Removal Tools (For both Machined or Stamped & Formed Contacts) | | | | |
|--|--|--|--|--|
| Part Number | Description | | | |
| ATRT-100 | Contact and Wedgelock Extraction Tool | | | |
| AT11-310-1605 | Contact Removal Tool, Plastic, Size 16 | | | |

| Sealing Plugs (For both Machined or Stamped & Formed Contacts) | | | | |
|--|---|--|--|--|
| Part Number | Description | | | |
| A114017 | Sealing Plug, Size 16, White | | | |
| A114017-SR | Sealing Plug, Size 16, SR01 Series, Black | | | |
| AT13-217-1605 | Locking Sealing Plug, Size 16, Grey | | | |
| AT13-217-1605-SR | Locking Sealing Plug, Size 16, SR01 Series, Red | | | |

| Stamped & Formed Contacts, Sockets & Pins | | | | | |
|---|--|---|---|--|--|
| Description | Size | AWG | Туре | | |
| Male Contact - Pin, Nickel-plated | 16 | 14-18 | Stamped & Formed | | |
| Female Contact - Socket, Nickel-plated | 16 | 14-18 | Stamped & Formed | | |
| Male Contact - Pin, Gold-plated | 16 | 14-18 | Stamped & Formed | | |
| Female Contact - Socket, Gold-plated | 16 | 14-18 | Stamped & Formed | | |
| Male Contact - Pin, Nickel-plated | 16 | 16-18 | Stamped & Formed | | |
| Female Contact - Socket, Nickel-plated | 16 | 16-18 | Stamped & Formed | | |
| Male Contact - Pin, Gold-plated | 16 | 16-18 | Stamped & Formed | | |
| Female Contact - Socket, Gold-plated | 16 | 16-18 | Stamped & Formed | | |
| Male Contact - Pin, Nickel-plated | 16 | 16-20 | Stamped & Formed | | |
| Female Contact - Socket, Nickel-plated | 16 | 16-20 | Stamped & Formed | | |
| Male Contact - Pin, Gold-plated | 16 | 16-20 | Stamped & Formed | | |
| Female Contact - Socket, Gold-plated | 16 | 16-20 | Stamped & Formed | | |
| Male Contact - Pin, Tin-plated | 16 | 16-20 | Stamped & Formed | | |
| Female Contact - Socket, Tin-plated | 16 | 16-20 | Stamped & Formed | | |
| Male Contact - Pin, Nickel-plated | 16 | 20-22 | Stamped & Formed | | |
| Female Contact - Socket, Nickel-plated | 16 | 20-22 | Stamped & Formed | | |
| Male Contact - Pin, Gold-plated | 16 | 20-22 | Stamped & Formed | | |
| Female Contact - Socket, Gold-plated | 16 | 20-22 | Stamped & Formed | | |
| | Description Male Contact - Pin, Nickel-plated Female Contact - Socket, Nickel-plated Male Contact - Pin, Gold-plated Female Contact - Socket, Gold-plated Male Contact - Pin, Nickel-plated Male Contact - Pin, Nickel-plated Male Contact - Socket, Nickel-plated Male Contact - Socket, Nickel-plated Male Contact - Socket, Gold-plated Female Contact - Socket, Gold-plated Male Contact - Pin, Nickel-plated Female Contact - Socket, Nickel-plated Male Contact - Pin, Gold-plated Female Contact - Socket, Gold-plated Male Contact - Pin, Tin-plated Female Contact - Pin, Tin-plated Male Contact - Pin, Nickel-plated Male Contact - Pin, Gold-plated | DescriptionSizeMale Contact - Pin, Nickel-plated16Female Contact - Socket, Nickel-plated16Male Contact - Pin, Gold-plated16Female Contact - Socket, Gold-plated16Male Contact - Pin, Nickel-plated16Female Contact - Pin, Nickel-plated16Male Contact - Pin, Gold-plated16Female Contact - Pin, Gold-plated16Male Contact - Pin, Mickel-plated16Female Contact - Socket, Gold-plated16Female Contact - Pin, Nickel-plated16Male Contact - Pin, Gold-plated16Female Contact - Socket, Gold-plated16Male Contact - Pin, Tin-plated16Female Contact - Pin, Tin-plated16Male Contact - Pin, Nickel-plated16Male Contact - Pin, Nickel-plated16Female Contact - Socket, Nickel-plated16Male Contact - Pin, Nickel-plated16Male Contact - Pin, Nickel-plated16Male Contact - Pin, Gold-plated16 | DescriptionSizeAWGMale Contact - Pin, Nickel-plated1614-18Female Contact - Socket, Nickel-plated1614-18Male Contact - Pin, Gold-plated1614-18Female Contact - Socket, Gold-plated1614-18Male Contact - Pin, Nickel-plated1616-18Female Contact - Socket, Nickel-plated1616-18Male Contact - Pin, Gold-plated1616-18Female Contact - Socket, Gold-plated1616-18Male Contact - Pin, Nickel-plated1616-20Female Contact - Socket, Nickel-plated1616-20Male Contact - Pin, Gold-plated1616-20Female Contact - Socket, Gold-plated1616-20Male Contact - Pin, Tin-plated1616-20Female Contact - Pin, Tin-plated1616-20Male Contact - Pin, Nickel-plated1616-20Male Contact - Socket, Tin-plated1616-20Male Contact - Pin, Nickel-plated1620-22Female Contact - Socket, Nickel-plated1620-22Male Contact - Pin, Gold-plated1620-22 | | |

| Tooling - Stamped & Formed Contacts | | | | |
|-------------------------------------|-------------------------------------|--|--|--|
| MFX-3950 | Crimp Die - Size 16, 18-20AWG | | | |
| MFX-3953 | Crimp Die - Size 16, 16-18AWG | | | |
| MFX-3975 | Crimp Die - Size 16, 14-16AWG | | | |
| MFX-3990 | Crimp Die - Size 16, 20-22AWG | | | |
| ATT-16-00 | Hand Crimp Tool - Size 16, 14-16AWG | | | |
| ATT-16-01 | Hand Crimp Tool - Size 16, 18-20AWG | | | |
| ATT-1612-03 | Hand Crimp Tool - Size 16, 20-22AWG | | | |