



Part No	Pin	A	B	C
WAFER-MX1.25-2PWB	2	1.25	7.50	
WAFER-MX1.25-3PWB	3	2.50	8.75	
WAFER-MX1.25-4PWB	4	3.75	10.00	2.50
WAFER-MX1.25-5PWB	5	5.00	11.25	3.75
WAFER-MX1.25-6PWB	6	6.25	12.50	5.00
WAFER-MX1.25-7PWB	7	7.50	13.75	6.25
WAFER-MX1.25-8PWB	8	8.75	15.00	7.50
WAFER-MX1.25-9PWB	9	10.00	16.25	8.75
WAFER-MX1.25-10PWB	10	11.25	17.50	10.00
WAFER-MX1.25-11PWB	11	12.50	18.75	11.25
WAFER-MX1.25-12PWB	12	13.75	20.00	12.50
WAFER-MX1.25-13PWB	13	15.00	21.25	13.75
WAFER-MX1.25-14PWB	14	16.25	22.50	15.00
WAFER-MX1.25-15PWB	15	17.50	23.75	16.25
WAFER-MX1.25-16PWB	16	18.75	25.00	17.50

NOTES:

- 1.BASE: LCP
- 2.PIN: Brass
- 3.Solder Tab: Brass

SPECIFICATIONS:

- 1.Spacing: 1.25
- 2.Voltage Rating: 125V AC DC
- 3.Current Rating: 1A AC DC
- 4.Insulation Resistance: 100MΩ Min
- 5.Contact Resistance: 20mΩ Max
- 6.Withstanding voltage: 500V AC 1/Minute
- 7.Temperatuer Range: -25℃ ~+ 85℃

MANUFACTURE DWG			东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd	
UNLESS OTHERWISE SPECIFIED TOLERANCES			TITLE: WAFER 1.25 贴片	
DECIMALS:	ANGLES:		PAR	WAFER-MX1.25-NPWB
X.:±0.2	X'.:±5°		DWN	
.X:±0.1	X.X':±3°		CHKD	
.XX:±0.05	X.XX':±1°	APVD	SCALE1:1	UNIT:MM
CUSTOMER COPY		SIZE:A4	SHEET:1F1	REV:A