FFA.00.250.CTAZ





Summary

Request a quote

Catalog				
Nb of contacts Coax	1			
Plug	Plug - Straight			
Locking system	Push-pull			
Suggested matching part	ERA.00.250.CTL			
Series	00 - NIM-CAMAC			

Technical details

Electrical Configuration

Nb of contacts Coax	1		
Contact Termination Coax	Solder		
R (max)	6.1 mOhm		
Insert configuration value	0.25 - 1 Coax (50 Ohm)		
Insulator	T: PTFE		
Rated current	4 A		
Impedance	50 Ohm		
VSWR	1.09 + 0.11 * f/GHz		
Vtest	2100 V (AC), 3000 V (DC)		
Contact Type	Coaxial 50 Ohm (Solder)		
Test voltage	2.1 kV (rms)		
Bucket Dia.	0.6 mm (0.024in)		
Contact Dia.	0.7 mm (0.028in)		
Form & Material			
Shell style / Model id	FFA - Straight plug with cable collet		
Plug	Straight		
Housing material	Brass (chrome plated [SAE AMS 2460]) shell and collet nut, nickel plated [SAE AMS QQ N 290] brass latch sleeve and mid pieces		
Locking system	Push-pull		
Keying	Circular, male		
Weight	2.57 g		
Environment			
Environmental sealing (IP rating)	IP50		
Endurance	5000 mating cycles		
F ret (min)	100 N		
Salt Spray Corrosion	>1000 hr		


LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMC components.

Cable fixation

Cable termination protection	For cable bend relief
Fixation type	Cable collet

Drawings







Dimensions

	A	L	M	
mm.	6.4	26	18	
in.	0.25	1.02	0.71	