

CROWN CLIP Junior

TE Internal #: 1551953-1

Board-to-Bus Bar, 2 Position, Bus Bar, Thermoplastic, Black, Mating Alignment, Box & Carton / Tray, Right Angle, CROWN CLIP Junior,

Busbar Connectors

View on TE.com >





Connectors > Power Connectors > Busbar Connectors











Connector System: Board-to-Bus Bar

Number of Positions: 2

Connector & Contact Terminates To: Bus Bar Mating Conductor Thickness: 3 mm [.118 in]

Contact Underplating Material Thickness

Housing Material: Thermoplastic

Features

Product Type Features

1 Todact Type Features	
Connector & Housing Type	Receptacle
Connector System	Board-to-Bus Bar
Connector & Contact Terminates To	Bus Bar
Configuration Features	
Number of Positions	2
PCB Mount Orientation	Right Angle
Mating & Unmating Configuration	Hot Pluggable
Electrical Characteristics	
Operating Voltage	600 VAC
Body Features	
Bus Bar Contact Plating Material	Tin
Contact Features	

1.27 μm[50 μin]



Contact Mating Area Plating Material Thickness	3 μm[118 μin]
Contact Mating Area Flating Material Thickness Contact Shape & Form	Multiple Contact Point
Contact Underplating Material	Nickel
Contact Base Material	Copper Alloy
Contact Base Material Contact Current Rating (Max)	170 A
Contact Length	31.4 mm[1.23 in]
Bus Bar Contact Style	Socket
Termination Features	
	F (0
Termination Post & Tail Length	5.68 mm[.224 in]
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Mating Alignment Type	Blindmate
Mating Alignment	With
Bus Bar Connector Mounting Retention	With
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Thermoplastic
Housing Color	Black
Dimensions	
Connector Height	28.25 mm[1.112 in]
	28.25 mm[1.112 in] 1.5 – 2 mm[.06 – .079 in]
Connector Height	
Connector Height PCB Thickness (Recommended)	1.5 – 2 mm[.06 – .079 in]
Connector Height PCB Thickness (Recommended) Product Width	1.5 – 2 mm[.06 – .079 in] 12 mm[.472 in]
Connector Height PCB Thickness (Recommended) Product Width Product Length	1.5 – 2 mm[.06 – .079 in] 12 mm[.472 in]
Connector Height PCB Thickness (Recommended) Product Width Product Length Usage Conditions	1.5 – 2 mm[.06 – .079 in] 12 mm[.472 in] 31.4 mm
Connector Height PCB Thickness (Recommended) Product Width Product Length Usage Conditions Operating Temperature Range	1.5 – 2 mm[.06 – .079 in] 12 mm[.472 in] 31.4 mm
Connector Height PCB Thickness (Recommended) Product Width Product Length Usage Conditions Operating Temperature Range Operation/Application	1.5 – 2 mm[.06 – .079 in] 12 mm[.472 in] 31.4 mm -55 – 105 °C[-67 – 221 °F]
Connector Height PCB Thickness (Recommended) Product Width Product Length Usage Conditions Operating Temperature Range Operation/Application Circuit Application	1.5 – 2 mm[.06 – .079 in] 12 mm[.472 in] 31.4 mm -55 – 105 °C[-67 – 221 °F]
Connector Height PCB Thickness (Recommended) Product Width Product Length Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards	1.5 – 2 mm[.06 – .079 in] 12 mm[.472 in] 31.4 mm -55 – 105 °C[-67 – 221 °F] Power
Connector Height PCB Thickness (Recommended) Product Width Product Length Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards Compatible With Agency/Standards Products	1.5 – 2 mm[.06 – .079 in] 12 mm[.472 in] 31.4 mm -55 – 105 °C[-67 – 221 °F] Power



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 240°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | CROWN CLIP Junior





Customers Also Bought



















Documents

Product Drawings

CCJ-Crown Clip Junior power connector

English

CAD Files

Customer View Model

ENG_CVM_CVM_1551953-1_A.2d_dxf.zip

English

3D PDF



3D

Customer View Model

ENG_CVM_CVM_1551953-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1551953-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Busbar Power Brochure

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English