

SENCITY® Spot-S circular polarized Planar Antenna 1308.99.0004

SPA-860/135/4/0/RCP

Description

SENCITY Spot-S planar antenna for 866 MHz ISM bands

Gain: 3.5 dBi

Polarization: circular - right hand

Frequency - band: 865 to 870 MHz

Half power beamwidth: 90° / 135° (vert. / hor.)

For outdoor or indoor mounting IP66 / IP67



Product Configuration

Technical Data

Electrical Data

	Band 1
Frequency (MHz)	865 - 870
VSWR	2
Impedance (Ohm)	50
Gain (dBi)	3.5
3dB beamwidth (h) (°)	135
3dB beamwidth (v) (°)	90
Vertical electrical tilt (°)	0

Ports

	Port 1
Connector	SMA, jack (female)
Polarization	circular right

General Data

DC Grounding	No
Composite Power max (W)	10

Mechanical Data

Dimensions (mm)	100 x 81 x 36 (Height x Width x Depth)
Weight (kg)	0.18
Windload	frontal: 15 N at km/h , Wind speed survival: km/h
Included mounting material	Wall mounting material

Environmental Data

Environmental conditions	outdoor
Operation temperature (°C)	-40 to 85
Storage temperature (°C)	-40 to 85
Transport temperature (°C)	-40 to 85
RoHS 2011/65/EU	compliant
REACH 2006/1907/EC	compliant

IP Rating: IP66 / IP67 (IEC 60529)

Material Data

Radome colour	RAL 7044 (grey)
Radome material	PC (Polycarbonate)

SENCITY® Spot-S circular polarized Planar Antenna 1308.99.0004

Related Products

9091.99.0238 Outdoor Spot-S Antenna Down-Sidetilt Bracket
9091.99.0237 L-Bracket for SPOT-S antennas

Related Documents

Mounting instruction	DOC-0000287053
Painting instruction	DOC-0000197967
Security instruction	DOC-0000278984
Outline drawing	DOU-00138514
3D-model	DOC-0000331433

Additional Information

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[1308.99.0004](#)