




Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > Ribbon Cable Connectors >

Crimp-on-Snap-in Housing



Connector System: **Wire-to-Board**
Number of Positions: **6**
Centerline (Pitch): **1.27 mm [.05 in]**
Row-to-Row Spacing: **2 mm [.059 in]**
Number of Rows: **2**

[All Crimp-on-Snap-in Housing \(9\)](#)

Features

Product Type Features

Ribbon Cable Connector Header Type	Shrouded
Connector Product Type	Housing
Connector System	Wire-to-Board
Connector & Housing Type	Plug
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	6
Number of Rows	2

Electrical Characteristics

Insulation Resistance	1000 MΩ
Operating Voltage	100 VAC

Body Features



Daisy Chain	Without
Primary Product Color	Red
Connector Profile	Standard

Contact Features

Contact Type	Socket
Contact Mating Area Plating Material	Tin
PCB Contact Termination Area Plating Material Finish	Matte
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Current Rating (Max)	1.5 A

Termination Features

Termination Method to Wire & Cable	Crimp & Snap
------------------------------------	--------------

Mechanical Attachment

Mating Alignment	With
Contact Retention Type Within Housing	Snap-In
PCB Mount Alignment	Without
Mating Alignment Type	Polarization
Mating Retention	With
Mating Retention Type	Contact Friction

Housing Features

Housing Material	PBT GF
Centerline (Pitch)	1.27 mm[.05 in]

Dimensions

Connector Length	10.9 mm[.429 in]
Connector Height	12.4 mm[.49 in]
PCB Thickness (Recommended)	1.6 mm[.06 in]
Row-to-Row Spacing	2 mm[.059 in]

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Signal
---------------------	--------



Industry Standards

UL Rating	Recognized
Compatible With Agency/Standards Products	UL
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	700
Packaging Method	Box & Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # CAT-M5833-F3492A
Female-on-Board Connector, Top Entry

TE Part # CAT-M5833-C8684A
Crimp Contacts - Micro-MaTch

TE Part # 7-215460-6
MICRO-MATCH FSID P

TE Part # 338070-6
MICRO-MATCH FEM.SE

TE Part # 7-188431-6
MM 6p FIB SMD connector

TE Part # 734870-2
CRIMP HT, MICRO-MATCH COSI, AW

TE Part # 215460-6
MICRO-MATCH FEM.SE

TE Part # 734870-1
CRIMP HT, MICRO-MATCH COSI, AW

TE Part # 100400-6
MICRO-MATCH FSID NP

TE Part # 5-1579008-3
EXTRACTION TOOL

TE Part # 7-100400-6
MICRO-MATCH FSID NP

Also in the Series | Micro-MaTch Industrial

Board-In Connectors(20)


Connector Contacts(4)

Insertion & Extraction Tools(1)

Pluggable I/O Cable Assemblies(52)

Ribbon Cable Connectors(183)

Customers Also Bought




TE Part #5069974006
CGPT-9.5/4.8-9-SP



TE Part #1-338095-2
MICRO-MATCH COSIHSG



TE Part #C20235-000
B-155-09



TE Part #5055556-9
10 POWER TAP ASSY .125



TE Part #343445-2
AMP-IN MINI (SPECIAL) 18.5-14 AWG



TE Part #280363
AMPMODU II REC. HSG, SINGLE ROW, 15 POS.



TE Part #643314-1
08P UMNL STR/REL



TE Part #HDP24-24-23PE-L017
REC, 23P, BLK, E, RNG, 16, P



TE Part #338096-1
MICRO-MATCH COSICNT



TE Part #254699-E
SRCA 2,54 6 M 1 SMD 137 E1 094 * GURT *

Documents

Product Drawings
MICRO-MATCH COSIHSG

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_338095-6_D_c-338095-6-d.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_338095-6_D_c-338095-6-d.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_338095-6_D_c-338095-6-d.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



Micro-MaTch Catalog

English

Ribbon Cable Interconnect Solutions

English

Centerline Micro-Match Connector Series

English

Product Specifications

micro-match crimp on snap in male on wire connector

English

Application Specification

English