


Part Number: 2140610150

Product Description: 2.4GHz / 5GHz Wi-Fi On-Metal Antenna, 150.00mm Cable Length, Compatible with U.FL / I-PEX MHF Connectors

Series Number: 214061

**Status:** Active

**Product Category: Antennas** 



#### **Documents & Resources**

### **Drawings**

<u>Drawing 2140610150\_sd.pdf</u> Packaging Design Drawing 2140610150-001.pdf

#### 3D Models and Design Files

<u>3D Model 2140610150\_stp.zip</u> HFSS Model 214061\_HFSS.zip

#### **Specifications**

Application Specification 2140610150-AS.pdf Product Specification 2140610150-PS.pdf

## **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# EU RoHS Certificate of Compliance

## **Part Details**

## General

Status	Active
Category	Antennas
Series	214061
Description	2.4GHz / 5GHz Wi-Fi On-Metal Antenna, 150.00mm Cable Length, Compatible with U.FL / I-PEX MHF Connectors
Component Type	On-metal Antenna with Cable
Function	Signal
Product Family	Internet of Things (IoT) Antennas: Wi-Fi, Bluetooth, Zigbee
Product Name	2.4/5GHz On-Metal Antenna
Protocol	BLE, BT, Thread, Wi-Fi, Wireless Hart, Zigbee
Туре	Internal, Wi-Fi Antenna
UPC	193264608393

## Electrical

Band#1 F_End (MHz)	2485
Band#1 F_Start (MHz)	2400
Band#2 F_End (MHz)	5850
Band#2 F_Start (MHz)	5150
Electrical Connectivity	Cable
Peak Gain (dBi)	3.8 @ 2.4 GHz, 6.4 @ 5 GHz
Return Loss - S11 (dB)	< -6, < -9
Total Efficiency	>55% @ 5 GHz, >60% @2.4 GHz

# Physical

Cable Length	150.00mm
--------------	----------

Length	20.20mm
Mounting Style	Adhesive
Net Weight	1.560/g
Packaging Type	Tray
Polarization	Linear
Radiation Pattern	Omnidirectional
Thickness	3.50mm
Width	20.20mm

This document was generated on Sep 23, 2024