

NEMA 5-15P PLUG

(1.68)

LENGTH "L"

(5.29)

NYLON COVER PLATE
COLOR: YELLOW

NEMA 5-15
SUPER-SAFEWAY
WATERTITE
DUAL-SIDED OUTLET BOX

POLYCARBONATE FLIP LIDS
COLOR: YELLOW

GFCI PLUG 15A/120V
RESET TYPE: MANUAL

(2.05)

12/3 SJOW/SJO CORD
YELLOW

RUBBER BOX
COLOR: YELLOW

(3.41)

(3.70)

(1.38)

(3.91)

TECHNICAL

LISTED: UL & CSA
 RATED SUPPLY VOLTAGE: 120VAC
 RATED CURRENT: UP TO 15 AMPS
 RESET TYPE: MANUAL
 OPERATING FREQUENCY: 60 Hz
 TYPE: CLASS A
 GROUND TRIP CURRENT: 4-6 mA
 OVERLOAD CURRENT: 90 AMP 125 VAC
 INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE
 ENDURANCE OPERATIONS: 3000 OPERATIONS
 GFCI ENCLOSURE: NEMA 3R

MATERIAL NUMBER	ENGINEERING NUMBER	LENGTH "L"
1301530080	15053W-2	2 FT. ± 1 IN.
1301530081	15053W-25	25 FT. ± 2 IN.
1301530086	15053W-50	50 FT. ± 4 IN.

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
$\frac{F}{A} = 0$ $\frac{E}{C} = 0$ $\frac{P}{D} = 0$	DIMENSION UNITS	SCALE	CURRENT REV DESC: NEW SALES DRAWING CREATED
	INCH	NTS	
	GENERAL TOLERANCES (UNLESS SPECIFIED)		
	ANGULAR TOL	±	°
	4 PLACES	±	
DIVISIONAL SYMBOLS	3 PLACES	±	EC NO: 686059
	2 PLACES	±	DRWN: PPURSUTANDEL 2021/11/16
	1 PLACE	±	CHK'D: DNGUYEN2 2021/12/01
	0 PLACES	±	APPR: HKNEELAND 2022/01/04
	INITIAL REVISION:		
	DRWN: PPURSUTANDEL	2021/11/16	molex 15A GFCI PLUG W/DUAL DUPLEX PRODUCT CUSTOMER DRAWING
	APPR: HKNEELAND	2022/01/04	
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	THIRD ANGLE PROJECTION	DRAWING SERIES
			C-SIZE 130153
	DOCUMENT NUMBER	CUSTOMER	DOC TYPE DOC PART REVISION
	1301530080	GENERAL MARKET	PSD 000 A
	SEE TABLE		SHEET NUMBER
			1 OF 1