

PANEL CUT-OUT		
Z	Y	X
0.70~1.25	10.50~10.70	28.9~29.1
1.25~2.00	10.50~10.70	29.1~29.2
2.00~3.00	10.50~10.70	29.2~29.3

NOTES:

1.Rating:

VDE ENEC 16(4)A 250V AC T85/55

KC 16(4)A 250V AC T85/55

CQC 16(4)A 250V AC T105/55

UL cUL 16GPA 125V AC/16GPA 250V AC T105/55

2.Circuit Diagram: 3P ON-OFF

3.Terminal Strength: $\geq 80N$

4.Electrical life: ≥ 10000 cycles

5.Withstand Voltage: Withstand Voltage:1500VAC 1min


Terminals to Button:3000VAC 1min

Leakage Current:1mA

6.Current resistance: $\leq 50m\Omega$ (initial)

7.Insulation resistance: $\geq 100M\Omega$

8.Body Materil: NYLON 66 94V-0~2



A4				普通公差:	深圳市华灿天禄电子有限公司								
A3				COMMON TOLERANCE :									
A2				UP TO 5	±0.20	单位	mm	投影		品名	跷板开关	比例	Free
A1				ABOVE 5 TO 30	±0.30	绘图	周金勇	核对	梁金勇	型号	RS606		
REV.	DATE	REVISION DESCRIPTION	ISSUE	ABOVE 30	±0.50	DRAWN BY		CHECKED BY		MODEL NO.			
				ANGULAR	±5°	日期	2015.09.15	核准	周培雷	图号	RS606-101N011CRB		
						DATE		APPROVAL BY		DWG NO.			