

# USB-A to USB-C Cable, Right-Angle USB-C, USB 2.0, (M/M), 6 ft. (1.83 m)

MODEL NUMBER: U038-006-CRA



USB-A to C cable connects a smartphone or other USB-C device to the USB-A port on your computer, wall charger or car charger.

## Features

**USB Type-A to USB Type-C Cable Connects a USB-C Mobile Device to Your Computer** This six-foot right-angle USB-C cable allows you to connect a device with a USB-C or Thunderbolt 3 port to a USB-enabled computer, charger, hard drive, hub or other peripheral for the purpose of charging, powering, syncing or transferring data. It is compatible with any device with a USB-C or Thunderbolt 3 port, including tablets, smartphones, MacBooks, Ultrabooks and Chromebooks.

**Transfers Data and Charges Devices at USB 2.0 Speeds** The USB-A to C cable supports USB 2.0 data transfer speeds up to 480 Mbps. The cable is backward compatible with previous USB generations, allowing you to use it with older equipment.

**Reversible USB-C Connector Attaches in Either Direction** Unlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for a fumble-free connection every time.

**Right-Angle USB-C Plug Makes Connecting in Tight Spaces Easier** The space-saving right-angle USB-C plug is easy to install in confined spaces, such as behind your computer desk or workstation. The right-angle construction also relieves strain on the cable and connector and prevents the cable from bending awkwardly.

## Specifications

| OVERVIEW    |                      |
|-------------|----------------------|
| UPC Code    | 037332214126         |
| Technology  | USB 2.0 (High Speed) |
| Cable Type  | Passive              |
| CONNECTIONS |                      |

## Highlights

- Right-angle USB-C plug permits easier connection in confined or hard-to-reach spaces
- Supports USB 2.0 speeds up to 480 Mbps to ensure efficient data transfers
- Reversible USB-C plug connects in either direction for immediate no-fuss use
- USB-A to USB-C cable compatible with all USB-A, USB-C and Thunderbolt 3 devices

## Applications

- Charge and sync a USB-C mobile device from a USB-A wall charger up to 6 ft. away
- Connect a printer or scanner to a desktop computer's hard-to-reach rear USB-C port
- Transfer data between an external hard drive or flash drive and your computer or laptop

## System Requirements

- Device with a USB-C or Thunderbolt 3 port
- Device with a USB-A port

## Package Includes

- U038-003-CRA USB Type-A to Type-C Cable, M/M, 6 ft.



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                                     |
|--------------------------------------|-------------------------------------|
| Side A - Connector 1                 | USB A (MALE)                        |
| Side B - Connector 1                 | USB C (MALE) - RIGHT ANGLE          |
| Connector Plating                    | Nickel                              |
| Contact Plating                      | Gold                                |
| Connector Style                      | Angled                              |
| <b>PHYSICAL</b>                      |                                     |
| Material of Construction             | PVC                                 |
| Cable Jacket Color                   | White                               |
| Cable Jacket Rating                  | VW-1                                |
| Cable Outer Diameter (OD)            | 3.5 mm                              |
| Cable Length (ft.)                   | 6                                   |
| Cable Length (m)                     | 1.83                                |
| Cable Length (in.)                   | 72                                  |
| Shipping Dimensions (hwd / in.)      | 9.00 x 7.00 x 0.50                  |
| Shipping Weight (lbs.)               | 0.08                                |
| Shipping Weight (kg)                 | 0.04                                |
| Unit Packaging Type                  | Polybag                             |
| <b>ENVIRONMENTAL</b>                 |                                     |
| Operating Temperature Range          | 32° to 113°F (0° to 45°C)           |
| Storage Temperature Range            | -40° to 158°F (-40° to 70°C)        |
| Operating Humidity Range             | 10% to 85% RH, Non-Condensing       |
| Storage Humidity Range               | 5% to 90% RH, Non-Condensing        |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                     |
| USB Specification                    | USB 2.0 (up to 480 Mbps)            |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                     |
| Product Compliance                   | RoHS; CE (Europe); REACH; FCC (USA) |
| <b>WARRANTY &amp; SUPPORT</b>        |                                     |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty           |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.