











SECT B-B




SECT A-A



D

2:1



A12	A11	A10	A9	A8	A7	A6	A5	A4	A3	A2	A1
GND	RX2+	RX2-	Vbus	SBU1	D-	D+	CC	Vbus	TX1-	TX1+	GND
GND	TX2+	TX2-	Vbus	Vconn			SBU2	Vbus	RX1-	RX1+	GND
B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12


P/N	R/C
U261-24XXN-4B0417	在C2与C3靠近IC的位置竖着贴一个（0欧姆电阻）

U261-24XXN-4B0417

C TYPE PLUG:

PCB:

A1+A12+B1+B12
(外壳与GND不短路)



1: Au
2: Ni

1: Au1u"
2: Au3u"
4: Au15u"
5: Au30u"

REMARKS:

1.CONTACT INSERTION AND WITHDRAW FORCE:

- 1.Insertion force: 5N-20N max.
2. Withdrawal force: 8N-20N.
- 3.Durability: 10000Cycles.

2.ELECTRIC PROPERTY:

- 1.Contact current rating: 3A.
- 2.Dielectric Strength: 100V AC(RMS).
- 3.Insulation Resistance: 100 megaohms min.
- 4.Contact resistance:
40mOhms MAX.FOR VBUS,GND AND OTHER CONTACT
50mOhms MAX.AFTER ENVIRONMENT TEST

3.AMBIENT TEMPERATURE:

- 1.Operating temperature: -55°C to +85°C.

6	Shrapnel	SUS T=0.10mm	
5	Shell	SUS T=0.15mm	Ovep-plating: Ni
4	Terminal	C7025 T=0.15mm	Ovep-plating: Au Ni/Sn
3	Latch	SUS T=0.4mm	
2	Housing	LCP	UL94-0
1	Housing Stopper	LCP	UL94-0
ITEM	DESCRIPTION	MATERIAL	REMARKS

DSND		SCALE: N/A	MODEL TYPE:
DWN		VIEW:	Type-C 3.1
CHKD		UNIT: mm/in	PART NO.:
APPD		SIZE: A4	DWG NO.:
			U261-24XXN-4B0417
		WEIGHT	SHEET
			1/1
		REVISION	A0

XKB

XKB INDUSTRIAL PRECISION CO.,LIMITED

www.helloxkb.com www.helloxkb.cn www.xk-dg.cn

UNSPECIFIED TOLERANCES

REVISIONS

DESCRIPTION

DATE

REVISED

APPROVED

ANGLAR	±5°
L≤ 4	±0.2
4<L≤ 16	±0.3
16<L≤ 63	±0.4
L> 63	±0.5

www.helloxkb.com www.helloxkb.cn www.xk-dg.cn

ΔX
ΔX
ΔX
MARK

日期
日期

文件工程章

广东星坤科技股份有限公司