# KUEP-3D15-125 - ACTIVE

#### Potter & Brumfield | Potter & Brumfield KUEP

TE Internal #: 9-1393113-9 General Purpose Power Relay, Monostable, 1.2 W Coil, 13000 ohm Coil Resistance, UL Coil Insulation Class B, Potter & Brumfield KUEP, Power Relays

View on TE.com >

Relays & Contactors > Relays > Power Relays



Relay Type: General Purpose Power Relay

Coil Magnetic System: Monostable

Coil Power Rating DC: 1.2 W

Coil Resistance: 13000  $\Omega$ 

Coil Special Features: UL Coil Insulation Class B

#### Features

#### **Product Type Features**

Relay Type

#### **Configuration Features**

Contact Special Features

connectivity

General Purpose Power Relay

Magnetic Blowout

| Coil Special Features                                   | UL Coil Insulation Class B |
|---|----------------------------|
| Contact Arrangement                                     | 1 Form X SPST-NO-DM        |
| Contact Number of Poles                                 | 1                          |
| Electrical Characteristics                              |                            |
| Insulation Initial Dielectric Between Open Contacts     | 1200 Vrms                  |
| Contact Limiting Making Current                         | 10 A                       |
| Contact Limiting Short-Time Current                     | 10 A                       |
| Contact Limiting Continuous Current                     | 10 A                       |
| Insulation Initial Dielectric Between Adjacent Contacts | 2200 Vrms                  |
| Insulation Initial Dielectric Between Contacts & Coil   | 2200 Vrms                  |
| Insulation Initial Resistance                           | 100 MΩ                     |
| Contact Limiting Breaking Current                       | 10 A                       |
| Coil Power Rating DC                                    | 1.2 W                      |
| Coil Resistance   | 13000 Ω                    |
| Coil Voltage Rating                                     | 125 VDC                    |
|   |                            |

**&** For support call+1 800 522 6752

General Purpose Power Relay, Monostable, 1.2 W Coil, 13000 ohm Coil Resistance, UL Coil Insulation Class B, Potter & Brumfield KUEP, Power Relays



| Contact Current Pating       | 10 A                    |
|------------------------------|-------------------------|
| Contact Current Rating       | IUA                     |
| Contact Switching Load (Min) | 300mA @ 12V             |
| Contact Voltage Rating       | 150 VDC                 |
| Body Features                |                         |
| Product Weight               | 85 g[2.988 oz]          |
| Contact Features             |                         |
| Contact Material             | AgCdO                   |
| Termination Features         |                         |
| Relay Connection Type        | Plug-In                 |
| Terminal Configuration       | Quick Connect Terminals |
| Mechanical Attachment        |                         |
| Product Mount Type           | Socket                  |
| Dimensions                   |                         |
| Product Width                | 35.71 mm[1.4 in]        |
| Product Length               | 38.89 mm[1.53 in]       |
| Product Height               | 48.41 mm[1.9 in]        |
|                              |                         |

### Usage Conditions

| Environmental Category of Protection    | RTI           |
|---|---------------|
| Environmental Ambient Temperature (Max) | 70 °C[158 °F] |
| Operating Temperature Range             | -45 – 70 °C   |
| Operation/Application                   |               |
| Current Type                            | DC            |
| Coil Magnetic System                    | Monostable    |
| Packaging Features                      |               |
| Packaging Method                        | Package       |
| Other                                   |               |
| Length Class (Mechanical)               | 35 – 40 mm    |
| Environmental Ambient Temperature Class | 50 – 70 °C    |
| Height Class (Mechanical)               | 40 – 50 mm    |
| Coil Power Rating Class                 | 1 – 1.5 W     |
| Width Class (Mechanical)                | 30 – 40 mm    |

General Purpose Power Relay, Monostable, 1.2 W Coil, 13000 ohm Coil Resistance, UL Coil Insulation Class B, Potter & Brumfield KUEP, Power Relays



Contact Current Class

16 A

#### Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant with Exemptions  |
|---|--|
| EU ELV Directive 2000/53/EC                   | Compliant  |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024<br>(241)<br>Candidate List Declared Against: JAN 2023<br>(233)<br>SVHC > Threshold:<br>Cadmium oxide (3.76% in Component Part)<br>Aticle Safe Usage Statements:<br>Use personal protective equipment as required. Do not eat, drink or smoke when<br>using this product. Recycle if possible and dispose of the article by following all<br>applicable governmental regulations relevant to your geographic location. |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per<br>homogenous material. Also BFR/CFR/PVC<br>Free  |
| Solder Process Capability                     | Not applicable for solder process capability   |
| Product Compliance Disclaimer                 |  |

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**



General Purpose Power Relay, Monostable, 1.2 W Coil, 13000 ohm Coil Resistance, UL Coil Insulation Class B, Potter & Brumfield KUEP, Power Relays





## Also in the Series | Potter & Brumfield KUEP



## Customers Also Bought



### Documents

**CAD** Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_9-1393113-9\_D.2d\_dxf.zip

English

General Purpose Power Relay, Monostable, 1.2 W Coil, 13000 ohm Coil Resistance, UL Coil Insulation Class B, Potter & Brumfield KUEP, Power Relays



Customer View Model

ENG\_CVM\_CVM\_9-1393113-9\_D.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_9-1393113-9\_D.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

KUEP Series Relay Datasheet

English

KU Sockets & Accessories

English

**Product Specifications Definitions General Purpose Relays** English

Agency Approvals UL

English