

# SanDisk Connected Solutions

Automotive / Commercial / Industrial



## iNAND Embedded Flash Drives

| Part Number           | Capacity | Interface | Operating Temp | Seq. R/W (MB/s) | Ran. R/W (IOPS) | Package     |
|-----------------------|----------|-----------|----------------|-----------------|-----------------|-------------|
| <b>Industrial</b>     |          |           |                |                 |                 |             |
| SDINBDG4-8G-I1        | 8GB      | 5.1 HS400 | -25°C to 85°C  | 300/40          | 17K/8K          | 11.5x13x0.8 |
| SDINBDG4-16G-I1       | 16GB     | 5.1 HS400 | -25°C to 85°C  | 300/80          | 25K/15K         | 11.5x13x0.8 |
| SDINBDG4-32G-I1       | 32GB     | 5.1 HS400 | -25°C to 85°C  | 300/150         | 25K/15K         | 11.5x13x1.0 |
| SDINBDG4-64G-I1       | 64GB     | 5.1 HS400 | -25°C to 85°C  | 300/150         | 25K/15K         | 11.5x13x1.2 |
| <b>Industrial XT</b>  |          |           |                |                 |                 |             |
| SDINBDG4-8G-XI1       | 8GB      | 5.1 HS400 | -40°C to 85°C  | 300/40          | 17K/8K          | 11.5x13x0.8 |
| SDINBDG4-16G-XI1      | 16GB     | 5.1 HS400 | -40°C to 85°C  | 300/80          | 25K/15K         | 11.5x13x0.8 |
| SDINBDG4-32G-XI1      | 32GB     | 5.1 HS400 | -40°C to 85°C  | 300/150         | 25K/15K         | 11.5x13x1.0 |
| SDINBDG4-64G-XI1      | 64GB     | 5.1 HS400 | -40°C to 85°C  | 300/150         | 25K/15K         | 11.5x13x1.2 |
| <b>OEM/Commercial</b> |          |           |                |                 |                 |             |
| SDINBDG4-8G           | 8GB      | 5.1 HS400 | -25°C to 85°C  | 300/40          | 17K/8K          | 11.5x13x0.8 |
| SDINADF4-16G-H        | 16GB     | 5.1 HS400 | -25°C to 85°C  | 290/150         | 3100/1800       | 11.5x13x0.9 |
| SDINBDG4-16G          | 16GB     | 5.1 HS400 | -25°C to 85°C  | 300/80          | 25K/15K         | 11.5x13x0.8 |
| SDINADF4-32G          | 32GB     | 5.1 HS400 | -25°C to 85°C  | 290/150         | 3100/1800       | 11.5x13x0.9 |
| SDINBDG4-32G          | 32GB     | 5.1 HS400 | -25°C to 85°C  | 300/150         | 25K/15K         | 11.5x13x1.0 |
| SDINADF4-64G          | 64GB     | 5.1 HS400 | -25°C to 85°C  | 290/150         | 3100/1800       | 11.5x13x1.0 |
| SDINBDG4-64G          | 64GB     | 5.1 HS400 | -25°C to 85°C  | 300/150         | 25K/15K         | 11.5x13x1.2 |
| SDINADF4-128G-H       | 128GB    | 5.1 HS400 | -25°C to 85°C  | 290/150         | 3100/1800       | 11.5x13x1.2 |
| <b>Automotive</b>     |          |           |                |                 |                 |             |
| SDINBDG4-8G-XA        | 8GB      | 5.1 HS400 | -40°C to 85°C  | 300/28          | 17K/7.8K        | 11.5x13x0.8 |
| SDINBDG4-16G-XA       | 16GB     | 5.1 HS400 | -40°C to 85°C  | 300/55          | 17K/7.8K        | 11.5x13x0.8 |
| SDINBDG4-32G-XA       | 32GB     | 5.1 HS400 | -40°C to 85°C  | 300/110         | 17K/7.8K        | 11.5x13x1.0 |
| SDINBDG4-64G-XA       | 64GB     | 5.1 HS400 | -40°C to 85°C  | 300/110         | 17K/7.8K        | 11.5x13x1.2 |
| <b>Automotive XT</b>  |          |           |                |                 |                 |             |
| SDINBDG4-8G-ZA        | 8GB      | 5.1 HS400 | -40°C to 105°C | 300/28          | 17K/7.8K        | 11.5x13x0.8 |
| SDINBDG4-16G-ZA       | 16GB     | 5.1 HS400 | -40°C to 105°C | 300/55          | 17K/7.8K        | 11.5x13x0.8 |
| SDINBDG4-32G-ZA       | 32GB     | 5.1 HS400 | -40°C to 105°C | 300/110         | 17K/7.8K        | 11.5x13x1.0 |
| SDINBDG4-64G-ZA       | 64GB     | 5.1 HS400 | -40°C to 105°C | 300/110         | 17K/7.8K        | 11.5x13x1.2 |
| <b>Connected Home</b> |          |           |                |                 |                 |             |
| SDINBDG4-8G-H         | 8GB      | 5.1 HS400 | -25°C to 85°C  | 300/40          | 17K/8K          | 11.5x13x0.8 |
| SDINBDG4-16G-H        | 16GB     | 5.1 HS400 | -25°C to 85°C  | 300/80          | 25K/15K         | 11.5x13x0.8 |
| SDINBDG4-32G-H        | 32GB     | 5.1 HS400 | -25°C to 85°C  | 300/150         | 25K/15K         | 11.5x13x1.0 |
| SDINBDG4-64G-H        | 64GB     | 5.1 HS400 | -25°C to 85°C  | 300/150         | 25K/15K         | 11.5x13x1.0 |

## USB Flash Drives



| Part Number                             | Capacity | Form Factor    | Category | Operating Temp |
|---|----------|----------------|----------|----------------|
| <b>Cruzer Fit USB Flash Drive</b>       |          |                |          |                |
| SDUFD33-008G                            | 8        | Low Profile    | USB 2.0  | 0°C to 45°C    |
| SDUFD33-016G                            | 16       | Low Profile    | USB 2.0  | 0°C to 45°C    |
| SDUFD33-032G                            | 32       | Low Profile    | USB 2.0  | 0°C to 45°C    |
| SDUFD33-064G                            | 64       | Low Profile    | USB 2.0  | 0°C to 45°C    |
| <b>Cruzer Edge USB Flash Drive</b>      |          |                |          |                |
| SDUFD51-008G                            | 8        | Compact Design | USB 2.0  | 0°C to 45°C    |
| SDUFD51-016G                            | 16       | Compact Design | USB 2.0  | 0°C to 45°C    |
| SDUFD51-032G                            | 32       | Compact Design | USB 2.0  | 0°C to 45°C    |
| SDUFD51-064G                            | 64       | Compact Design | USB 2.0  | 0°C to 45°C    |
| SDUFD43-016G                            | 16       | Compact Design | USB 3.0  | 0°C to 45°C    |
| <b>Connected Home Time Shift Buffer</b> |          |                |          |                |
| SDUFDEC-016G                            | 16       | Low Profile    | USB 2.0  | 0°C to 55°C    |

SD Cards



| SKU                   | Capacity | Class | Interface | Max Speed | Operating Temp | Seq. R/W (MB/s) | TBW |
|-----------------------|----------|-------|-----------|-----------|----------------|-----------------|-----|
| <b>Automotive XT</b>  |          |       |           |           |                |                 |     |
| SDSDAG3-008G-XA       | 8        | U1    | SD 3.0    | UHS-I 104 | -40°C to 85°C  | 70/15           |     |
| SDSDAG3-016G-XA       | 16       | U1    | SD 3.0    | UHS-I 104 | -40°C to 85°C  | 70/30           |     |
| SDSDAG3-032G-XA       | 32       | U1    | SD 3.0    | UHS-I 104 | -40°C to 85°C  | 70/50           |     |
| SDSDAG3-064G-XA       | 64       | U1    | SD 3.0    | UHS-I 104 | -40°C to 85°C  | 70/50           |     |
| <b>Industrial</b>     |          |       |           |           |                |                 |     |
| SDSDAF3-008G-I        | 8        | U1    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 70/15           | 24  |
| SDSDAF3-016G-I        | 16       | U1    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 70/30           | 48  |
| SDSDAF3-032G-I        | 32       | U1    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 70/50           | 96  |
| SDSDAF3-064G-I        | 64       | U1    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 70/50           | 192 |
| <b>Industrial XT</b>  |          |       |           |           |                |                 |     |
| SDSDAF3-008G-XI       | 8        | U1    | SD 3.0    | UHS-I 104 | -40°C to 85°C  | 70/15           | 24  |
| SDSDAF3-016G-XI       | 16       | U1    | SD 3.0    | UHS-I 104 | -40°C to 85°C  | 70/30           | 48  |
| SDSDAF3-032G-XI       | 32       | U1    | SD 3.0    | UHS-I 104 | -40°C to 85°C  | 70/50           | 96  |
| SDSDAF3-064G-XI       | 64       | U1    | SD 3.0    | UHS-I 104 | -40°C to 85°C  | 70/50           | 192 |
| <b>OEM/Commercial</b> |          |       |           |           |                |                 |     |
| SDSDAA-008G           | 8        | 4     |           | UHS-I 50  | -25°C to 85°C  |                 |     |
| SDSDAE-008G           | 8        | U1    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 80/30           |     |
| SDSDAA-016G           | 16       | 4     | SD 3.0    | UHS-I 50  | -25°C to 85°C  |                 |     |
| SDSDAD-016G           | 16       | U1    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 80/10           |     |
| SDSDAE-016G           | 16       | U3    | SD 4.0    | UHS-I 104 | -25°C to 85°C  | 80/50           |     |
| SDSDAA-032G           | 32       | 4     |           | UHS-I 50  | -25°C to 85°C  |                 |     |
| SDSDAD-032G           | 32       | U1    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 80/10           |     |
| SDSDAE-032G           | 32       | U3    | SD 4.0    | UHS-I 104 | -25°C to 85°C  | 80/50           |     |
| SDSDAD-064G           | 64       | U1    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 80/10           |     |
| SDSDAE-064G           | 64       | U3    | SD 4.0    | UHS-I 104 | -25°C to 85°C  | 80/50           |     |
| SDSDAD-128G           | 128      | U1    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 80/50           |     |
| SDSDAE-128G           | 128      | U3    | SD 4.0    | UHS-I 104 | -25°C to 85°C  | 80/50           |     |
| <b>Connected Home</b> |          |       |           |           |                |                 |     |
| SDSDEC-004G           | 4        | U3    | SD 5.0    | UHS-I 104 | -0°C to 85°C   | 50/50           | 200 |
| SDSDEB-008G           | 8        | U1    | SD 5.0    | UHS-I 104 | -0°C to 85°C   | 50/10           | 80  |
| SDSDEB-016G           | 16       | U1    | SD 5.0    | UHS-I 104 | -0°C to 85°C   | 50/20           | 160 |
| SDSDEC-032G           | 32       | 10    | SD 3.0    | UHS-I 50  | -0°C to 85°C   | 30/30           | 450 |
| SDSDEB-032G           | 32       | U3    | SD 4.0    | UHS-I 104 | -0°C to 85°C   | 50/30           | 224 |
| SDSDEB-064G           | 64       | U3    | SD 4.0    | UHS-I 104 | -0°C to 85°C   | 50/30           | 448 |
| SDSDEB-128G           | 128      | U3    | SD 4.0    | UHS-I 104 | -0°C to 85°C   | 50/30           | 896 |

microSD Cards



| SKU                         | Capacity | Class | Interface | Max Speed | Operating Temp | Seq. R/W (MB/s) | TBW |
|-----------------------------|----------|-------|-----------|-----------|----------------|-----------------|-----|
| <b>Industrial Wide Temp</b> |          |       |           |           |                |                 |     |
| SDSDQAF-008G-I              | 8        | U1    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 70/15           | 16  |
| SDSDQAF-016G-I              | 16       | U1    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 70/50           | 32  |
| SDSDQAF2-032G-I             | 32       | 10    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 70/50           | 96  |
| SDSDQAF2-064G-I             | 64       | 10    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 70/50           | 192 |
| SDSDQAF3-128G-I             | 128      | U3    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 70/50           | 384 |
| <b>OEM/Commercial</b>       |          |       |           |           |                |                 |     |
| SDSDQAB-016G                | 16       | 4     | SD 3.0    | UHS-I 50  | -25°C to 85°C  | 20/5            |     |
| SDSDQAD-016G                | 16       | U1    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 40/10           |     |
| SDSDQAB-032G                | 32       | 4     | SD 3.0    | UHS-I 50  | -25°C to 85°C  | 20/5            |     |
| SDSDQAD-032G                | 32       | U1    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 40/10           |     |
| SDSDQAE-032G                | 32       | V30   | SD 5.0    | UHS-I 104 | -25°C to 85°C  | 80/50           |     |
| SDSDQAB-064G                | 64       | 4     | SD 3.0    | UHS-I 50  | -25°C to 85°C  | 20/5            |     |
| SDSDQAD-064G                | 64       | U1    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 40/10           |     |
| SDSDQAE-064G                | 64       | V30   | SD 5.0    | UHS-I 104 | -25°C to 85°C  | 80/50           |     |
| SDSDQAD-128G                | 128      | U1    | SD 3.0    | UHS-I 104 | -25°C to 85°C  | 40/10           |     |
| SDSDQAE-128G                | 128      | V30   | SD 5.0    | UHS-I 104 | -25°C to 85°C  | 80/50           |     |
| SDSDQAD-200G                | 200      | U1    | SD 3.0    | UHS-I 50  | -25°C to 85°C  | 80/10           |     |
| SDSDQAD-256G                | 256      | U1    | SD 5.0    | UHS-I 104 | -25°C to 85°C  | 95/10           |     |
| <b>Connected Home</b>       |          |       |           |           |                |                 |     |
| SDSDQEC-004G                | 4        | U3    | SD 5.0    | UHS-I 104 | -25°C to 85°C  | 50/50           | 200 |
| SDSDQEC-008G                | 8        | U3    | SD 5.0    | UHS-I 104 | 0°C to 85°C    | 50/50           | 400 |
| SDSDQEB-008G                | 8        | U1    | SD 5.0    | UHS-I 104 | 0°C to 85°C    | 50/10           | 80  |
| SDSDQEC-016G                | 16       | U3    | SD 5.0    | UHS-I 104 | 0°C to 85°C    | 50/50           | 800 |
| SDSDQEB-016G                | 16       | U1    | SD 5.0    | UHS-I 104 | 0°C to 85°C    | 50/20           | 160 |
| SDSDQEB-032G                | 32       | U3    | SD 5.0    | UHS-I 104 | 0°C to 85°C    | 50/30           | 320 |
| SDSDQEB-064G                | 64       | U3    | SD 5.0    | UHS-I 104 | 0°C to 85°C    | 50/30           | 640 |

**NOT FOR NEW DESIGN**

## iNAND Embedded Flash Drives

| Part Number          | Capacity | Interface  | Operating Temp | Seq. R/W (MB/s) | Ran. R/W (IOPS) | Package     |
|----------------------|----------|------------|----------------|-----------------|-----------------|-------------|
| <b>Automotive</b>    |          |            |                |                 |                 |             |
| SDIN8DE2-4G-A        | 4GB      | 4.51 HS200 | -25°C to 85°C  | 90/17           | 4500/500        | 11.5x13x1.0 |
| SDIN8DE1-8G-A        | 8GB      | 4.51 HS200 | -25°C to 85°C  | 120/37          | 4500/1200       | 11.5x13x1.0 |
| SDIN8DE2-8G-A        | 8GB      | 4.51 HS200 | -25°C to 85°C  | 120/37          | 4500/1200       | 11.5x13x1.0 |
| SDIN8DE2-16G-A       | 16GB     | 4.51 HS200 | -25°C to 85°C  | 120/37          | 4500/1200       | 11.5x13x1.0 |
| SDIN8DE4-32G-A       | 32GB     | 4.51 HS200 | -25°C to 85°C  | 120/37          | 4500/1200       | 11.5x13x1.0 |
| SDIN8DE4-64G-A       | 64GB     | 4.51 HS200 | -25°C to 85°C  | 120/37          | 4500/1200       | 11.5x13x1.0 |
| <b>Automotive XT</b> |          |            |                |                 |                 |             |
| SDIN8DE2-4G-XA       | 4GB      | 4.51 HS200 | -40°C to 85°C  | 90/17           | 4500/500        | 11.5x13x1.0 |
| SDIN8DE1-8G-XA       | 8GB      | 4.51 HS200 | -40°C to 85°C  | 90/17           | 4500/850        | 11.5x13x1.0 |
| SDIN8DE2-8G-XA       | 8GB      | 4.51 HS200 | -40°C to 85°C  | 115/30          | 4500/850        | 11.5x13x1.0 |
| SDIN8DE2-16G-XA      | 16GB     | 4.51 HS200 | -40°C to 85°C  | 115/30          | 4500/1200       | 11.5x13x1.0 |
| SDIN8DE4-32G-XA      | 32GB     | 4.51 HS200 | -40°C to 85°C  | 120/37          | 4500/1200       | 11.5x13x1.2 |
| SDIN8CE4-64G-XA      | 64GB     | 4.51 HS200 | -40°C to 85°C  | 120/37          | 4500/1200       | 12x16x1.4   |
| <b>Industrial</b>    |          |            |                |                 |                 |             |
| SDIN8DE2-4G-I        | 4GB      | 4.51 HS200 | -25°C to 85°C  | 90/17           | 4500/500        | 11.5x13x1.0 |
| SDIN8DE1-8G-I        | 8GB      | 4.51 HS200 | -25°C to 85°C  | 120/37          | 4500/1200       | 11.5x13x1.0 |
| SDIN8DE2-8G-I        | 8GB      | 4.51 HS200 | -25°C to 85°C  | 120/37          | 4500/1200       | 11.5x13x1.0 |
| SDIN8DE2-16G-I       | 16GB     | 4.51 HS200 | -25°C to 85°C  | 120/37          | 4500/1200       | 11.5x13x1.0 |
| SDIN8DE4-32G-I       | 32GB     | 4.51 HS200 | -25°C to 85°C  | 120/37          | 4500/1200       | 11.5x13x1.0 |
| SDIN8DE4-64G-I       | 64GB     | 4.51 HS200 | -25°C to 85°C  | 120/37          | 4500/1200       | 11.5x13x1.0 |
| <b>Industrial XT</b> |          |            |                |                 |                 |             |
| SDIN8DE2-4G-XI       | 4GB      | 4.51 HS200 | -40°C to 85°C  | 90/17           | 4500/500        | 11.5x13x1.0 |
| SDIN8DE1-8G-XI       | 8GB      | 4.51 HS200 | -40°C to 85°C  | 90/17           | 4500/850        | 11.5x13x1.0 |
| SDIN8DE2-8G-XI       | 8GB      | 4.51 HS200 | -40°C to 85°C  | 115/30          | 4500/850        | 11.5x13x1.0 |
| SDIN8DE2-16G-XI      | 16GB     | 4.51 HS200 | -40°C to 85°C  | 115/30          | 4500/1200       | 11.5x13x1.0 |
| SDIN8DE4-32G-XI      | 32GB     | 4.51 HS200 | -40°C to 85°C  | 120/37          | 4500/1200       | 11.5x13x1.2 |
| SDIN8CE4-64G-XI      | 64GB     | 4.51 HS200 | -40°C to 85°C  | 120/37          | 4500/1200       | 12x16x1.4   |

### Contact Information

For all inquiries, please email:  
[OEMProducts@SanDisk.com](mailto:OEMProducts@SanDisk.com)

For more information,  
 please visit:  
[www.sandisk.com](http://www.sandisk.com)

Sales and Technical Information:  
[techsupport@SanDisk.com](mailto:techsupport@SanDisk.com)

**USA** | Western Digital Technologies, Inc  
 Corporate Headquarters  
 951 SanDisk Drive  
 Milpitas, CA 95035  
 Tel: +1-408-801-1000  
 Fax: +1-408-801-8657

**Japan**  
 Shinagawa Tokyu Bldg., 3F  
 1-6-31, Konan, Minato-ku  
 Tokyo, Japan 108-0075  
 Tel: +81-3-4334-7110 (OEM Sales)

**Taiwan**  
 37F, Taipei 101 Tower, No 7  
 Xinyi Road, Section 5  
 Taipei, Taiwan, 110  
 Tel: +886-2-8758-2966  
 Fax: +886-2-8758-2999

**Europe**  
 7 Atir Yeda St.  
 Kfar Saba 44425, Israel  
 Tel: + 972-9-764-5000  
 Fax: + 972-3-548-8666

**Korea**  
 9F, Asia Tower,  
 430 Nonhyeon-Ro  
 Gangnam Gu, Seoul 135-719, Korea  
 Tel: + 82-2-6718-4600  
 Fax: + 82-2-3452-9145

**China**  
 Room 121-122, Bldg. 2  
 International Commerce & Exhibition Ctr.  
 Hong Hua Rd. Futian Free Trade Zone  
 Shenzhen, China  
 Tel: +86-755-8348-5218  
 Fax: +86-755-8348-5418



Western Digital Technologies, Inc. | 951 SanDisk Drive | Milpitas | CA 95035 | USA

©2017 Western Digital Corporation or its affiliates. All rights reserved. SanDisk and iNAND are trademarks of Western Digital Corporation or its affiliates, registered in the United States and other countries. Android is a trademark of Google Inc. The microSD, microSDHC and microSDXC marks and logos are trademarks of SD-3C, LLC. Other brand names mentioned herein are for identification purposes only and may be the trademark(s) of their respective holder(s).

Western Digital Technologies, Inc. is the seller of record and licensee in the Americas of SanDisk® products.

AUTO-COM-INDUST\_DIST1\_2\_082917

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## SanDisk:

[SDSDAA-032G](#) [SDSDAA-004G-J](#) [SDSDAA-016G](#) [SDSDAA-004G](#) [SDSDAA-008G-J](#) [SDSDAA-016G-J](#) [SDSDAA-032G-J](#) [SDSDAA-008G](#) [SD8SBAT-032G](#) [SD8SBAT-128G](#) [SD8SFAT-064G-1122](#) [SD8SBAT-032G-1122](#) [SD8SNAT-064G-1122](#) [SD8SBAT-064G](#) [SD8SBAT-064G-1122](#) [SD8SFAT-032G](#) [SD8SFAT-128G](#) [SD8SNAT-064G](#) [SD8SNAT-128G](#) [SD8SBAT-256G-1122](#) [SD8SMAT-128G-1122](#) [SD8SNAT-256G](#) [SD8SFAT-128G-1122](#) [SD8SBAT-256G](#) [SD8SFAT-032G-1122](#) [SD8SNAT-256G-1122](#) [SD8SBAT-128G-1122](#) [SD8SFAT-064G](#) [SD8SNAT-128G-1122](#) [SD8SMAT-064G](#) [SD8SMAT-032G](#) [SD8SMAT-128G](#) [SD7SN3Q-064G-1122](#) [SD7SB3Q-064G-1122](#) [SD7UN3Q-512G-1122](#) [SD7UB3Q-256G-1122](#) [SD7UN3Q-128G-1122](#) [SD7UB2Q-512G-1122](#) [SD7UB3Q-128G-1122](#) [SD7UB2Q-010T-1122](#) [SD7UN3Q-256G-1122](#) [SDIN8DE1-8G](#) [SDIN8CE4-128G](#) [SDIN8DE4-32G](#) [SDIN7DP4-16G](#) [SDIN9DS2-64G](#) [SDIN8DE2-8G](#) [SDIN8DE2-16G](#) [SDIN9DS2-32G](#) [SDIN7DP2-4G](#) [SDIN8DE4-64G](#) [SD7SB7S-512G-1122](#) [SD7SN6S-256G-1122](#) [SD7SB6S-256G-1122](#) [SD7SB7S-010T-1122](#) [SD7SF6S-128G-1122](#) [SD7SB6S-128G-1122](#) [SD7SF6S-256G-1122](#) [SD7SF6S-512G-1122](#) [SD7SN6S-512G-1122](#) [SD7SN6S-128G-1122](#) [SD6SB2M-512G-1022I](#) [SD6SB2M-256G-1022I](#) [SD6SB2M-128G-1022I](#) [SDIN8DE1-8G-A](#) [SDIN8DE4-32G-XI](#) [SDIN8DE4-32G-I](#) [SDIN8DE2-4G](#) [SDIN8DE1-8G-XI](#) [SDIN8DE1-8G-Q](#) [SDIN8DE1-8G-I](#) [SDIN8DE2-16G-I](#) [SDIN8DE2-4G-A](#) [SDIN8DE2-4G-Q](#) [SDIN8DE2-4G-XA](#) [SDIN8DE2-16G-Q](#) [SDIN8DE4-64G-Q](#) [SDIN8DE4-32G-A](#) [SDIN8DE2-8G-XA](#) [SDIN8DE2-4G-I](#) [SDIN8DE4-64G-A](#) [SDIN8DE2-8G-A](#) [SDIN8DE2-16G-XA](#) [SDIN8DE4-16G](#) [SDIN8DE4-32G-Q](#) [SDIN8DE4-64G-I](#) [SDIN8DE2-16G-A](#) [SDIN8DE2-4G-XI](#) [SDIN8DE4-32G-XA](#) [SDIN8DE2-16G-XI](#) [SDIN8DE1-8G-XA](#) [SDSDAG-016G-XA](#) [SDSDAG-008G-XA](#) [SDSDAG-032G-XA](#) [SDSDAG-064G-XA](#) [SD7SB3Q-128G](#) [SD7SB3Q-256G](#) [SD8SB8U-512G](#) [SD8SB8U-128G](#) [SD8SN8U-256G](#)