

3-1534799-1 ✓ ACTIVE

AMP DUOPLUG

TE Internal #: 3-1534799-1

Wire-to-Board, 11 Position, 2.5 mm [.098 in] Centerline, Insulation


Displacement (IDC), 1 Row, Natural, PA 6 GF, Standard Edge

Connectors

[View on TE.com >](#)



Connectors > PCB Connectors > Card Edge Connectors > Standard Edge Connectors



Connector System: **Wire-to-Board**

Number of Positions: **11**

Centerline (Pitch): **2.5 mm [.098 in]**

Termination Method to Wire & Cable: **Insulation Displacement (IDC)**

Number of Rows: **1**

Features

Product Type Features

Connector System	Wire-to-Board
Connector & Housing Type	Receptacle
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Card Entry Style	Side
Compatible With Wire & Cable Type	Discrete Wire
Number of Positions	11
Number of Rows	1
Connector Contact Load Condition	Selectively Loaded
PCB Mount Orientation	Right Angle

Electrical Characteristics

Operating Voltage	50 VAC, 250 VAC
-------------------	-----------------

Body Features

Primary Product Color	Natural
-----------------------	---------



Contact Features

Contact Retention Within Housing	With
Contact Type	Socket
Contact Mating Area Plating Material Thickness	3 – 6 µm
Contact Mating Area Plating Material	Tin
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Tin
Contact Current Rating (Max)	2 A

Termination Features

Termination Method to Wire & Cable	Insulation Displacement (IDC)
------------------------------------	-------------------------------

Mechanical Attachment

Mating Alignment Type	Keyed
Mating Retention	Without
Mating Alignment	With
Contact Retention Type Within Housing	Locking Lance
PCB Mount Alignment	With
PCB Mount Retention	Without
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Entry Configuration	Both Ends Open
Centerline (Pitch)	2.5 mm [.098 in]
Housing Material	PA 6 GF

Dimensions

Card Slot Depth	5.05 mm
Connector Height	7.3 mm [.287 in]
PCB Thickness (Recommended)	1.5 mm [.059 in]
Compatible Insulation Diameter Range	1.2 – 1.4 mm [.047 – .055 in]
Wire Size	.22 – .35 mm ²

Usage Conditions

Operating Temperature Range	-40 – 110 °C [-40 – 230 °F]
-----------------------------	-----------------------------

Operation/Application

Circuit Application	Signal
---------------------	--------



Industry Standards

UL Flammability Rating	UL 94V-2
Glow Wire Rating	GWEPT 750°C (Without Flame)

Packaging Features

Packaging Quantity	1232
Packaging Method	Box

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 3-1534798-9
AMP DUOPLUG MARK II
CONNECTOR3-20P SELEC



TE Part # 4-1534796-4
AMP DUOPLUG MARK II
CONNECTOR 4 POS. KEY



TE Part # 2-1740918-3
AMP DUOPLUG2.5 MKII 3P W. PCB
LOCK



TE Part # 1-1740501-3
AMP DUOPLUG 2.5 MKII 3P W. PCB
LOCK



TE Part # 1-1740918-3
AMP DUOPLUG2.5 MKII 3P W. PCB
LOCK



TE Part # 1-1534799-9
DUOPLUG MK II SELECTIVE LOADED



TE Part # 3-1534799-3
AMP DUOPLUG MARK II CONNEC.
SELEC.LOADED



TE Part # 4-1534799-3
AMP DUOPLUG MARK II CONNEC.
SELEC.LOADED



TE Part # 6-1534799-1
AMP DUOPLUG MK2 CONNECTOR
11P SELECTIVE


Customers Also Bought



TE Part #6-1241961-2
STD TIM HOUSING MKII 2POS




TE Part #3-1534798-9
AMP DUOPLUG MARK II
CONNECTOR3-20P SELEC




TE Part #3-1534796-4
AMP DUOPLUG MK2 CONNECTOR
4P S




TE Part #3-1534798-7
AMP DUOPLUG MK2 CONNECTOR
7P SELECTIVE



TE Part #3-1534797-1
AMP DUOPLUG MK2 CONNECTOR
11P



TE Part #3-1534796-6
AMP DUOPLUG MK2 CONNECTOR 6P



TE Part #3-1534796-8
AMP DUOPLUG MK2 CONNECTOR 8P



TE Part #3-1241961-1
2POS STANDARD TIMER HOUSING



Documents

Product Drawings

[AMP DUOPLUG MK2 CONNECTOR 11P SELECTIVE](#)

English

CAD Files

Customer View Model

[ENG_CVM_CVM_3-1534799-1_A.2d_dxf.zip](#)

English

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_3-1534799-1_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_3-1534799-1_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[RAST Connector System Catalog](#)

English

Product Specifications

[Application Specification](#)

English

Agency Approvals

[VDE Certificate](#)

English

[VDE Certificate](#)

English