

Numeric Profinet Data Display

- Compact 96 x 24 mm panel mount numeric unit
- Display Profinet PN data inputs
- 6 digit, 13 mm red LED display
- Rugged metal case
- IP65 front panel with supplied gasket
- 24 VDC supply




RS Stock Number 8967730

Description	Model	Part Number
6-digit Profinet data display	MI-PAN-PN6R13	KPN1LE1-I8121462

Specifications

Display	Six 7-segment, 13 mm red LEDs
Interface	Profinet IO RT
Display characters	0 to 9, A, b, c, d, E, F, G, H, I, J, L, n, o, P, q, r, S, t, u, y, -, ., (,)
Addresses	device name
Baud rate	100 Mbit/s
Front protection	IP65 with supplied gasket
Dimensions	96 x 24 mm, depth 60 mm
Panel cut-out	93 x 22.2 mm
Mounting	Screw clamps
Operating temperature	0 to +50 °C
Storage temperature	-25 to +70 °C
Power supply	24 VDC ± 20 %, 75 mA

Dimensions:



microSYST

Also available:

- Numeric and Profibus Serial data displays
- Alpha-Numeric Profibus and Serial data displays

Digits	Character height G	B	H	D	E	T
	mm	mm	mm	mm	mm	mm
6	13	96	24	91.5	20	60