

PIN RECEPTACLES

**FOR .015" - .020" DIAMETER PINS (#1 CONTACT)
AND .015" - .022" DIAMETER PINS (#2 CONTACT)
(SEE SPECIFIC CONTACT RANGE ON PAGE 251)**

<p>4716 4716-0-15-XX-21-XX-10-0 Solder mount in .038 min. mounting hole</p>	<p>6553 6553-0-15-XX-11-XX-10-0 Hex press-fit in .041 plated through-hole</p>	<p>5743 5743-0-15-XX-21-27-10-0 Surface mount</p>
<p>6577 6577-0-15-XX-21-XX-10-0 Solder mount in .043 min. mounting hole</p>	<p>0777 0777-0-15-XX-11-XX-10-0 Hex press-fit in .042 plated through-hole</p>	<p>7545 7545-0-15-XX-21-XX-10-0 Press-fit in .043 mounting hole</p>

SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard
Contact Material: Beryllium Copper Alloy 172, HT
Dimensions: Inches
Tolerances On: Lengths: $\pm .005$
 Diameters: $\pm .002$
 Angles: $\pm 2^\circ$



ORDER CODE: XXXX - 0 - 15 - XX - X1 - XX - 10 - 0

BASIC PART #

SPECIFY SHELL FINISH:

- 01 200 μ " TIN/LEAD OVER NICKEL
- ◆ 80 200 μ " TIN OVER NICKEL (RoHS)
- ◆ 15 10 μ " GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

- 02 100 μ " TIN/LEAD OVER NICKEL
- ◆ 84 100 μ " TIN OVER NICKEL (RoHS)
- ◆ 27 30 μ " GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#11 or #21 CONTACT (DATA ON PAGE 251)

(For alternate contact choices, see group A on page 248)

