

Ordering Information:

A2001WR-XP - ** / 2 - ** / 3 - ** / 4 - ** / 5 - ** / 6 - ** / 7

1.PartNO.

2.Style:

(Blank): Type 1

2: Type 2

3.Material:

(Blank): Nylon 66,UL94V-0(White)

GWT: Nylon 66,UL94V-0(Beige),IEC 60335-1,5th EditionGlow Wire Capable.

4.Color:

(Blank): see section 3 Material

(Blank): White RD: Red

GN: Green BK: Black

5.Finish:

(Blank): Tin over Nickel

G: Gold over Nickel

6.Size D:

(Blank): Type 1,D=3.40mm


D23: Type 2,D=2.30mm

D34: Type 2,D=3.40mm

7.Packing:

(Blank): Bag

TU: Tube



SPECIFICATIONS:

Current Rating: 3A AC,DC (MAX)

Voltage Rating: 100V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 10mΩ Max.

Insulation Resistance: 1000MΩ Min.

Withstanding Voltage: 800V AC/minute

Pin Material: Brass

Ordering Information & Dimensions

Part NO.	Dimensions(mm)	
	A	B
A2001WR-2P	2.00	6.00
A2001WR-3P	4.00	8.00
A2001WR-4P	6.00	10.00
A2001WR-5P	8.00	12.00
A2001WR-6P	10.00	14.00
A2001WR-7P	12.00	16.00
A2001WR-8P	14.00	18.00
A2001WR-9P	16.00	20.00
A2001WR-10P	18.00	22.00
A2001WR-11P	20.00	24.00
A2001WR-12P	22.00	26.00
A2001WR-13P	24.00	28.00
A2001WR-14P	26.00	30.00
A2001WR-15P	28.00	32.00
A2001WR-16P	30.00	34.00
A2001WR-17P	32.00	36.00
A2001WR-18P	34.00	38.00
A2001WR-19P	36.00	40.00
A2001WR-20P	38.00	42.00

CJTconn CHANGJIANG CONNECTORS CO.,LTD.

REV	DESCRIPTION	DATE
A4	CHANGE THE DRAWING	2022.03.08
A3	CHANGE THE STRUCTURE	2021.11.11
A2	CHANGE THE DRAWING	2020.06.01
A1	CHANGE THE STRUCTURE	2015.06.23
A0	NEW RELEASE	2005.05.10

Unit	Scale	Sheet
mm	5:1	1 of 1
DRWN	CHK'D	APPR
Haisen Li	Diankui Wan	Jack Yin
General Tolerances		THIRD ANGLE PROJECTION
x.xx±0.25		
x.xxx±0.20		
x.xxxx±0.15		
ANGLES ±1°		

TITLE		DRAWING NO.	REV
2.00mm PITCH 90° WAFER			