

Buchanan

TE Internal #: 796984-8

Header, Wire-to-Board, 8 Position, 5.08 mm [.2 in] Centerline, 1 Row, 90° Wire Entry Angle, 30 – 12 AWG Wire Size, PCB Terminal

Blocks

View on TE.com >





Connectors > Terminal Blocks & Strips > PCB Terminal Blocks











Terminal Block Connector Type: Header

Connector System: Wire-to-Board

Number of Positions: 8

Centerline (Pitch): 5.08 mm [.2 in]

Number of Rows: 1

Features

Product Type Features

Wire Protection	With
Terminal Block Connector Type	Header
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Stacked Levels	Level 1/Level 2
Wire Entry Location	Side
Stacking Configuration	Side Stackable
Number of Positions	8
Number of Rows	1
Wire Entry Angle	90°
Electrical Characteristics	
Operating Voltage	300 VAC



Primary Product Color Product Orientation Vertical Contact Features Contact Mating Area Plating Material Contact Base Material Contact Base Material Contact Current Rating (Max) 17.5 A Termination Features Termination Fost & Tail Length Termination Method to PCB Through Hole - Solder Mechanical Attachment Screw Plating Material Screw Plating Material Screw Material Brass Thread Size M3 Connector Mounting Type Board Mount Housing Features Housing Material PA 66 Centerline (Pitch) Dimensions Wire Size Usage Conditions Operating Lemperature Range Operation/Application Circuit Application Circuit Application Circuit Application Circuit Marking Matking Color Packaging Features Packaging Features Packaging Features Packaging Guantity P5 Packaging Method Carton		
Contact Mating Area Plating Material Contact Base Material Brass Contact Current Rating (Max) 17.5 A Termination Peatures Termination Post & Tail Length Termination Method to PCB Through Hole Solder Mechanical Attachment Screw Plating Material Screw Material Brass Thread Size M3 Connector Mounting Type Board Mount Housing Features I lousing Material PA 66 Centerline (Pitch) Dimensions Wire Size Usage Conditions Operating Temperature Range Operation/Application Circuit Application Circuit Application Centerline Centerline Centerline Centerline Centerline Contact Material Power & Signal Centerline Center	Primary Product Color	Black
Contact Mating Area Plating Material Contact Base Material Brass Contact Current Rating (Max) 17.5 A Termination Features Termination Post & Tail Length Termination Method to PCB Through Hole Solder Mechanical Attachment Screw Plating Material Screw Material Brass Thread Size M3 Connector Mounting Type Board Mount Housing Features Housing Material PA 66 Centerline (Pitch) Dimensions Wire Size 0.05 = 1.4 mm² Usage Conditions Operating Temperature Range 40 - 120 °C(40 - 248 °F) Operation/Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Features Packaging Quantity 95	Product Orientation	Vertical
Contact Base Material Brass Contact Current Rating (Max) 17.5 A Termination Features Termination Post & Tail Length 3.8 mm[.15 in] Termination Method to PCB Through Hole Solder Mechanical Attachment Screw Plating Material Nickel Screw Material Brass Thread Size M3 Connector Mounting Type Board Mount Housing Features Housing Material PA 66 Centerline (Pitch) 5.08 mm[.2 in] Dimensions Wire Size JS - 1.4 mm² Usage Conditions Operating Temperature Range -40 – 120 °C[.40 – 248 °F] Operation/Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Features Packaging Quantity 95	Contact Features	
Termination Features Termination Post & Tail Length 3.8 mm[.15 in] Termination Method to PCB Through Hole - Solder Mechanical Attachment Screw Plating Material Nickel Screw Material Brass Thread Size M3 Connector Mounting Type Board Mount Housing Features Housing Material PA 66 Centerline (Pitch) 5.08 mm[.2 in] Dimensions Wire Size .05 – 1.4 mm² Usage Conditions Operating Temperature Range -40 – 120 °C[-40 – 248 °F] Operation/Application Circuit Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Features Packaging Quantity 95	Contact Mating Area Plating Material	Tin
Termination Features Termination Post & Tail Length 3.8 mm[.15 in] Termination Method to PCB Through Hole - Solder Mechanical Attachment Screw Plating Material Nickel Screw Material Brass Thread Size M3 Connector Mounting Type Board Mount Housing Features Housing Material PA 66 Centerline (Pitch) 5.08 mm[.2 in] Dimensions Wire Size .05 – 1.4 mm² Usage Conditions Operation/Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Features Packaging Quantity 95	Contact Base Material	Brass
Termination Post & Tail Length Termination Method to PCB Through Hole Solder Mechanical Attachment Screw Plating Material Screw Material Nickel Screw Material Brass Thread Size M3 Connector Mounting Type Board Mount Housing Features Housing Material PA 66 Centerline (Pitch) 5.08 mm[,2 in] Dimensions Wire Size Usage Conditions Operation/Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Guantity 95	Contact Current Rating (Max)	17.5 A
Termination Method to PCB Mechanical Attachment Screw Plating Material Screw Material Screw Material Screw Material Screw Material Screw Material Thread Size M3 Connector Mounting Type Board Mount Housing Features Housing Material PA 66 Centerline (Pitch) Dimensions Wire Size Usage Conditions Operating Temperature Range Operating Temperature Range 40 – 120 °C[40 – 248 °F] Operation/Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Features Packaging Quantity 95	Termination Features	
Mechanical Attachment Screw Plating Material Screw Material Brass Thread Size M3 Connector Mounting Type Board Mount Housing Features Housing Material PA 66 Centerline (Pitch) Dimensions Wire Size Usage Conditions Operating Temperature Range Operation/Application Circuit Application Power & Signal Identification Marking Marking Color Packaging Features Packaging Quantity 95	Termination Post & Tail Length	3.8 mm[.15 in]
Screw Plating Material Brass Thread Size M3 Connector Mounting Type Board Mount Housing Features Housing Material PA 66 Centerline (Pitch) 5.08 mm(,2 in) Dimensions Wire Size .05 – 1.4 mm² Usage Conditions Operating Temperature Range -40 – 120 °C[-40 – 248 °F] Operation/Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Peatures Packaging Quantity 95	Termination Method to PCB	Through Hole - Solder
Screw Material Brass Thread Size M3 Connector Mounting Type Board Mount Housing Features Housing Material PA 66 Centerline (Pitch) 5.08 mm[.2 in] Dimensions Wire Size .05 – 1.4 mm² Usage Conditions Operating Temperature Range -40 – 120 °C[40 – 248 °F] Operation/Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Features Packaging Features	Mechanical Attachment	
Thread Size Connector Mounting Type Board Mount Housing Features Housing Material PA 66 Centerline (Pitch) 5.08 mm[.2 in] Dimensions Wire Size 0.55 – 1.4 mm² Usage Conditions Operating Temperature Range 40 – 120 °C[-40 – 248 °F] Operation/Application Circuit Application Circuit Application Marking Color White Packaging Features Packaging Quantity 95	Screw Plating Material	Nickel
Connector Mounting Type Housing Features Housing Material PA 66 Centerline (Pitch) Dimensions Wire Size Usage Conditions Operating Temperature Range Operation/Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Features Packaging Quantity Board Mount Board Mount Board Mount PA 66 5.08 mm[.2 in] 5.08 mm[.2 in] -40 - 1.4 mm² -40 - 1.20 °C[-40 - 248 °F] White	Screw Material	Brass
Housing Features Housing Material PA 66 Centerline (Pitch) 5.08 mm[.2 in] Dimensions Wire Size .05 – 1.4 mm² Usage Conditions Operating Temperature Range -40 – 120 °C[-40 – 248 °F] Operation/Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Features Packaging Quantity 95	Thread Size	M3
Housing Material PA 66 Centerline (Pitch) 5.08 mm[.2 in] Dimensions Wire Size .05 – 1.4 mm² Usage Conditions Operating Temperature Range -40 – 120 °C[-40 – 248 °F] Operation/Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Features Packaging Quantity 95	Connector Mounting Type	Board Mount
Centerline (Pitch) Dimensions Wire Size .05 – 1.4 mm² Usage Conditions Operating Temperature Range -40 – 120 °C[-40 – 248 °F] Operation/Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Features Packaging Quantity 95	Housing Features	
Dimensions Wire Size .05 – 1.4 mm² Usage Conditions Operating Temperature Range -40 – 120 °C[-40 – 248 °F] Operation/Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Features Packaging Quantity 95	Housing Material	PA 66
Wire Size Usage Conditions Operating Temperature Range -40 – 120 °C[-40 – 248 °F] Operation/Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Features Packaging Quantity 95	Centerline (Pitch)	5.08 mm[.2 in]
Usage Conditions Operating Temperature Range -40 – 120 °C[-40 – 248 °F] Operation/Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Features Packaging Quantity 95	Dimensions	
Operating Temperature Range -40 – 120 °C[-40 – 248 °F] Operation/Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Features Packaging Quantity 95	Wire Size	.05 – 1.4 mm ²
Operation/Application Circuit Application Power & Signal Identification Marking Marking Color White Packaging Features Packaging Quantity 95	Usage Conditions	
Circuit Application Power & Signal Identification Marking Marking Color White Packaging Features Packaging Quantity 95	Operating Temperature Range	-40 - 120 °C[-40 - 248 °F]
Identification Marking Marking Color White Packaging Features Packaging Quantity 95	Operation/Application	
Marking Color Packaging Features Packaging Quantity 95	Circuit Application	Power & Signal
Packaging Features Packaging Quantity 95	Identification Marking	
Packaging Quantity 95	Marking Color	White
	Packaging Features	
Packaging Method Carton	Packaging Quantity	95
	Packaging Method	Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (.61% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought





TE Part #1-5745968-5 25 PLUG SP/FMS SCRLK




TE Part #EM63332001 BATTU-12.7/6.1-A1-3-STK




TE Part #3-1625999-0 HSC100 39R 5%





TE Part #1-796692-2 TERMI-BLOK PCB MOUNT 1&2 12P.5



TE Part #1986660-2 2 Posn Power Connector, Green, 10.16 mm



TE Part #ZPF00000000100856 Rectangular Connector Receptacles, Tool-less Assembly





Documents

Product Drawings

8 POS TERMI-BLOK PCB MOUNT 1&2

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_796984-8_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_796984-8_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_796984-8_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the $\pmb{\mathsf{Terms}}$ and $\pmb{\mathsf{Conditions}}$ of use.

Datasheets & Catalog Pages



BUCHANAN TERMINAL BLOCKS CATALOG - EUROSTYLE TERMINAL BLOCKS

English

1-1773458-1_EURO_STYLE_TERMINAL_BLOCKS_QRG

English

Product Specifications

Application Specification

English

Agency Approvals

UL

English