


# Accessories

## Actuation kit (puck)

### BTS-DSU35-EB1




- End position damped
- Switch pins made of stainless steel (1.4305)
- For clockwise or counterclockwise rotating drives
- Displays rotatable by 90 °
- Hole pattern on flange: 30 × 80 mm (30 × 130 mm)
- Connection shaft (shaft extension) height: 20 mm (30 mm)/Ø: max. 30 mm
- Maximum slide ring diameter: 34 mm


#### General description

Dual sensors are especially designed for position detection in rotary actuators. They combine the reliability of non-contact inductive sensors with the flexibility of a modular housing system. A broad range of practice-oriented accessories ensure optimal adaption to your system.

Type	BTS-DSU35-EB1
ID	6900225
Design	Accessories for dual sensors, Ni4-DSU35...
Housing material	Plastic, PP-GF30
Tightening torque fixing screw	1.5 Nm
Included in delivery	2 × hex cap screws M5 × 12, 2 × D5 lock washers, 1 × countersunk screw M6 × 25



**Accessories**

Type code	Ident-No.		Dimension drawing
BTS-DSU35-CLIP/YE	6900429	Yellow display clips, suitable for BTS-DSU35-EB actuators, packaging unit: 10	
BTS-DSU35-CLIP/BK	6900430	Black display clips, suitable for BTS-DSU35-EB actuators, packaging unit: 10	