

KNIPEX Crimp Assortments



- sturdy construction
- secure transport
- stackable



New KNIPEX Crimp Assortments, in TANOS MINI-systainers



Contents of the new assortments

Article-No. EAN-Code Pliers			Conne	ctors	Δ'Δ	
	4003773-			'		g
97 90 21 NEW	062134)		Cable Connectors style and description as per	1420
	97	52 36)		Article-No. (25 pcs. each) 97 99 01 / 02 / 14 / 15 /	
97 90 22 NEW	062141				16 / 17 / 18 / 34 / 35 (20 pcs. each) 97 99 21 / 22 / 36	1550
,,,,,						
	97	52 36	12 42 195			
97 90 23 NEW	062158)	P	200 pcs. each 0.5 / 0.75 / 1.0 / 1.5 / 2.5 mm ²	1220
	97	52 38			100 pcs. each 4.0 / 6.0 mm ²	
97 90 24 NEW	062394			, <u> </u>	200 pcs. each 0.5 / 0.75 / 1.0 / 1.5 / 2.5 mm ²	1355
0000		2 L L 2			100 pcs. each 4.0 / 6.0 mm ² / 50 pcs. 10.0 mm ²	
	97	53 08	12 42 195			

Contents of the established assortments in new TANOS MINI-systainers

Article-No. EAN-Code		e Pliers			Connectors				
	4003773-					a			
97 90 00	025375		=		Cable Connectors (25 pcs. each) style and description as per	1450			
		7 00 215 A	•		Article-No. 97 99 01 / 02 / 04 / 07 /				
97 90 01	025382	APPA	•		09 / 14 / 16 / 17 / 20 / 21 / 34 / 35	1180			
	97	7 32 225	•						
97 90 05	025535	WAO.	•	//	200 pcs. each 0.5 / 0.75 / 1.0 / 1.5 / 2.5 mm ²	945			
	93	7 71 180	•	1	150 pcs. each 4.0 / 6.0 mm ² ; 50 pcs. each 10.0 / 16.0 mm ²				
97 90 06	025542	WYO.	-	So.	200 pcs. each 0.5 / 0.75 / 1.0 / 1.5 mm ² ; 150 pcs. 2.5 mm ²	1015			
	97	7 71 180	-		75 pcs. each 4.0 / 6.0 mm ² ; 50 pcs. 10.0 mm ² ; 40 pcs. 16.0 mm	12			
97 90 07	026877	DELF(-)-	•		500 pcs. each 0.5 / 0.75 / 1.0 / 1.5 / 2.5 mm ²	830			
	97	7 61 145 F	•	1					
97 90 08	026990	mil)		s s	300 pcs. each 0.5 / 0.75 / 1.0 / 1.5 mm ²	840			
	97	7 61 145 F	•	1	200 pcs. 2.5 mm ²				
97 90 09	028574			S	200 pcs. each 0.5 / 0.75 / 1.0 / 1.5 / 2.5 mm ²	1170			
	97	7 53 04			100 pcs. each 4.0 / 6.0 mm ² ; 50 pcs. 10.0 mm ²				
97 90 10	046202	- C		s s	200 pcs. each 0.5 / 0.75 / 1.0 / 1.5 / 2.5 mm ²	1360			
	9:	7 53 04	12 40 200		100 pcs. each 4.0 / 6.0 mm ² ; 50 pcs. 10.0 mm ²				
97 90 12	048916			F.	200 pcs. each 0.5 / 0.75 / 1.0 / 1.5 / 2.5 mm ²	1430			
	97	7 53 08	12 40 200	1	100 pcs. each 4.0 / 6.0 mm ² ; 50 pcs. 10.0 mm ²				



97 Crimping Pliers "PreciForce"



97 52 36



97 52 38

- ► for solder-free electrical connections
- repetitive, high crimping quality due to precision dies and integral lock (selfreleasing mechanism)
- ► these tools have been set precisely (calibrated) in the factory
- ▶ high transmission of force thanks to lever action for fatique-reduced working
- good handling thanks to favourable handle position, low weight, short design and ergonomically shaped handles
- ► all stressed parts are made of special steel, oil-hardened and tempered
- ► head burnished, two-colour dual component handles



The new Crimping Pliers provide a very good handling and amazingly high leverage despite the compact size. Particularly favourable for larger cross sections.



97 52 30



97 52 35











several boxes can be connected with each other


Article-No.	EAN-	Range o	Range of Application		Capacity			7,7
	Code	•			•		Length	
	4003773-				mm²	AWG	mm	g
97 52 30	051855		non-insulated butt connectors		1.5-10.0	15-7	220	490
97 52 33	051862	5	non-insulated ter		0.5-10.0	20-7	220	490
97 52 34	051879	لكع	non-insulated	4.8 mm	0.1-2.5	27-13	220	490
97 52 35	051886		open plug-type connectors	6.3 mm	0.5-6.0	20-10	220	490
97 52 36	051893		insulated termina and connectors	ls	0.5-6.0	20-10	220	490
97 52 38	051909		end sleeves (ferrules)		0.5-6.0	20-10	220	490
97 52 50	051916		COAX-BNC-Connectors RG 58, 174, 188, 316				220	490
97 49 94 97 49 95	030947 031000	and a	locator for 97 52 locator for 97 52					

KNIPEX

12 "Multistrip 10", Self-Adapting Universal Insulation Stripper

Documents of the content of the cont

Article-No.	EAN-	Stripping capacities		47
Length	Code	•		
mm		mm²	AWG	g
12 42 195	054580	0.03-10.0	32-7	300
12 49 21	057581	spare blades		
12 49 22	057598	spare clamping jaws		
12 49 23	057604	spare length stop		



Precise stripping from 0.03 up to 10.0 mm²


- ► fully automated adjustment to the respective cross-sectiondepending insulation thicknesses in a range from 0.03 – 10.0 mm²
- ▶ the so far common fine adjustment of the tool is no longer necessary due to the unique self-infeeding of the cutting depth preventing damage to the conductor
- the steel-made restrain jaws with integrated cutting edges very often also allow professional stripping of cables with demanding insulating materials like PTFE and Radox®
- with wire cutter for copper and aluminium wires, multiple stranded up to 10 mm² and single stranded up to 6 mm²
- smoothly operating mechanism
- easily interchangeable screwon style blades, length stop and restrain jaws with cutting edges



Opens automatically once the stripping operation is completed

Specia

The cutting edges at the steel clamping jaws (1) firmly restrain the insulated cable and avoid skidding. The stripping blades (2) cut to the correct depth and remove the insulation cleanly without any manual adjustment.



- body made of tough fibreglass reinforced plastic
- ergonomic soft compound zone in the handle area for a secure grip

Radox® is a registered trademark of Huber & Suhner AG

Steel restrain jaws with cutting edges

avoid skidding of the cable

Distributed by:

L100 01705/01/02.06/7.000/GB

KNIPEX-Werk C. Gustav Putsch KG

Oberkamper Straße 13 42349 Wuppertal Germany

Phone: +49 202 47 94-0 Fax: +49 202 47 74 94

Internet: www.knipex.de E-Mail: info@knipex.de