Effective June 2017 Supersedes October 2012

GLD/GBA 1/4" x 1-1/4" (6.3 mm x 32 mm) Pin indicating fast acting fuse





Product features

• GLD/GBA

- o GLD-albaloy-plated indicating pin
- GBA-red indicating pin
- Non-Time-Delay: Indicating
- Amp Rating: 1/2 to 15 Amps

Agency information:

- CE, UL Listed, Std. 248-14
- 1/2-5 A/125 Vac, 10 kA AIC
- Guide JDYX, File E19180
- UL Recognized, 6 A/125 Vac, 1 kA

AIC

- 10-15 A/50 Vac/dc, 300 AIC
- Guide JDYX2, File E19180
- CSA Certified, 1/2-5 A/125 Vac, 10 kA

AIC



Class 1422-01, File 53787



0.255" Max 0.249" Mir

GLD-½	GLD-2	GLD-6
GLD-¾	GLD-3	GLD-10
GLD-1	GLD-4	GLD-12
GLD-1-½	GLD-5	GLD-15
GBA-½	GBA-2	GBA-6
GBA-¾	GBA-3	GBA-10
GBA-1	GBA-4	GBA-15
GBA-1-½	GBA-5	

Carton Quantity and Weight

Amp Ratings	Carton Qty.	Weight	
		Lbs.	Kg.
1⁄2-15	100	0.86	0.390

General Information:

- Use in power electronic circuits in which a fuse opening must be quickly apparent.
- Opening of fuse results in the ejection of end pin.
- Type GLD has an albaloy-plated pin for positive, electrical signal circuit activation.
- Type GBA has a red pin for high visibility.
- The Cooper Bussmann Series 8000 fuse blocks are recommended for visual indication.
- For visual indication use Cooper Bussmann panel-mounted fuse holder HLD (15 A maximum)
- Ferrules: Nickel-plated brass end caps.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin

Eaton

Electronics Division 1000 Eaton Boulevard Cleveland, OH 44122 United States Eaton.com/electronics



© 2017 Eaton All Rights Reserved Printed in USA Publication No. 2012 BU-SB12694 June 2017

Eaton is a registered trademark.

All other trademarks are property of their respective owners

AMP RATING S 100 10 IN SECONDS TIME .1 .01 0 100 CURRENT IN AMPS

200

BUSSMANN

Time-Current Characteristic Curves-Average Melt