

Technical Data Sheet

Thermal Transfer Hybrid Ribbon

This specification is intended to outline the physical and chemical properties of *PANDUIT*'s black thermal transfer hybrid ribbon and include the following part numbers.

Ribbon Part Number		
RHH4BL-Z	TTRH-BL	RMH2BL
RHH2BL-S	TTRH2-BL	RMH4BL
RHH4BL-S	RMEH2BL	RMEH4BL

PRODUCT SPECIFICATIONS:**Ribbon Property**

Base Film Caliper:	4.5 μ m
Ink Color:	Black.
Ink Formulation:	Pigmented Wax/Resin
Ink Coating Weight	3.80 g/sq.m

Ribbon is free from coating voids, skips, wrinkles or other conditions which would adversely affect the transfer integrity.

Printing Property

Optimal Print:	Thermal transfer printing should occur in the temperature range of 41 ⁰ F – 95 ⁰ F (5 ⁰ C – 35 ⁰ C) at 30% - 85% R.H
Usage Condition:	41 ⁰ F – 95 ⁰ F (5 ⁰ C-35 ⁰ C) at 30% - 85% R.H
Storage Condition:	Keep indoor, avoiding high temperature (such as beside heat source), high humidity, and direct sunlight.
Storage Life:	One year at storage conditions.

Ribbon components are not considered health hazards, except when exposed to fire.

Features:

1. Exceptional smudge and scratch resistance
2. Produces high print quality normal, rotated and two dimensional bar codes, logos and graphics



18900 Panduit Drive
Tinley Park, IL 60487
Customer Service: 800-777-3300

TDS: HYBRID
RIBBON
Date: 17Jul12
Revision: 3

Technical Data Sheet

LIMITED WARRANTY

All *PANDUIT* Identification Solution Products (except for Software programs) are warranted to be free from defects in material and workmanship at the time of sale but our obligation under this warranty is limited to replacement of the product proved to be defective within 6 months from the date of sale, or in the case of printers, within 90 days from the date of sale. This warranty is void if the products or printers are modified, altered or misused in any way. Use of *PANDUIT* printers with any product other than the specified *PANDUIT* products for which the printer was designed constitutes misuse. Before using, the user shall determine the suitability of the product for its intended use and user assumes all risk and liability whatsoever in connection therewith. The foregoing may not be altered except by an agreement signed by officers or seller and manufacturer.

NEITHER *PANDUIT* OR SELLER SHALL BE LIABLE FOR ANY OTHER INJURY, LOSS OR DAMAGE, WHETHER DIRECT OR CONSEQUENTIAL, ARISING OUT OF THE USE OF, OR THE INABILITY TO USE THE PRODUCT OR THE PRINTER.

THIS WARRANTY IS MADE IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES, EXPRESS OR IMPLIED. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS OF PARTICULAR USE ARE SPECIFICALLY EXCLUDED.

The information contained in this literature is based on our experience to date and is believed to be reliable. It is intended as a guide or use by persons having technical skill at their own discretion and risk. We do not guarantee favorable results or assume any liability in connection with its use. Dimensions contained herein are for reference purposes only. This publication is not to be taken as a license to operate under, or a recommendation to infringe any existing patents. This supersedes and voids all previous literature, etc.