

PJM13P40PA

P-Channel Enhancement Mode Power MOSFET

Product Summary

- $V_{DS} = -40V, I_D = -13A$
- $R_{DS(on)} < 14.3m\Omega @ V_{GS} = -10V$
- $R_{DS(on)} < 22m\Omega @ V_{GS} = -4.5V$



Features

- Advanced Trench Technology
- 100% Avalanche Tested
- RoHS and Reach Compliant
- Halogen and Antimony Free
- Moisture Sensitivity Level 3

Application


- Load Switch
- PWM Applications
- Power Management

Marking Code



Pin	Description
1,2,3	Source
4	Gate
5,6,7,8	Drain

Schematic Diagram




Absolute Maximum Ratings

Ratings at 25°C ambient temperature unless otherwise specified.

Parameter	Symbol	Value	Unit
Drain-Source Voltage	$-V_{DS}$	40	V
Gate-Source Voltage	$-V_{GS}$	± 20	V
Drain Current-Continuous	$-I_D$	13	A
Drain Current-Pulsed ^{Note1}	$-I_{DM}$	48	A
Maximum Power Dissipation	P_D	3.5	W
Junction Temperature	T_J	150	°C
Storage Temperature Range	T_{STG}	-55 to +150	°C

Thermal Characteristics

Maximum Junction-to-Ambient ^{Note2}	R_{eJA}	36	°C/W
--	-----------	----	------



PJM13P40PA

P-Channel Enhancement Mode Power MOSFET

Electrical Characteristics

(Ta=25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	-V _{(BR)DSS}	V _{GS} =0V, I _D =-250μA	40	--	--	V
Zero Gate Voltage Drain Current	-I _{DSS}	V _{DS} =-40V, V _{GS} =0V	--	--	1	μA
Gate-Body Leakage Current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V	--	--	±100	nA
Gate Threshold Voltage ^{Note3}	-V _{GS(th)}	V _{DS} =V _{GS} , I _D =-250μA	1	1.6	2.5	V
Drain-Source On-Resistance ^{Note3}	R _{DS(on)}	V _{GS} =-10V, I _D =-10A	--	9	14.3	mΩ
		V _{GS} =-4.5V, I _D =-10A	--	13	22	mΩ
Forward Transconductance ^{Note3}	g _{FS}	V _{DS} =-5V, I _D =-4A	--	22	--	S
Dynamic Characteristics						
Input Capacitance	C _{iss}	V _{DS} =-15V, V _{GS} =0V, f=1MHz	--	3800	--	pF
Output Capacitance	C _{oss}		--	370	--	pF
Reverse Transfer Capacitance	C _{rss}		--	315	--	pF
Gate Resistance	R _g	V _{DS} =0V, f=1MHz	--	5	--	Ω
Switching Characteristics						
Turn-on Delay Time	t _{d(on)}	V _{DD} =-20V, V _{GS} =-10V I _D =-12A, R _{GEN} =2.5Ω	--	10	--	nS
Turn-on Rise Time	t _r		--	21	--	nS
Turn-off Delay Time	t _{d(off)}		--	53	--	nS
Turn-off Fall Time	t _f		--	29	--	nS
Total Gate Charge	Q _g	V _{DS} =-20V, V _{GS} =-10V I _D =-12A	--	42	--	nC
Gate-Source Charge	Q _{gs}		--	7.3	--	nC
Gate-Drain Charge	Q _{gd}		--	8.5	--	nC
Source-Drain Diode Characteristics						
Diode Forward Voltage ^{Note3}	-V _{SD}	V _{GS} =0V, I _s =-10A	--	0.8	1.2	V
Diode Forward Current ^{Note2}	-I _s		--	--	13	A

Note: 1. Repetitive Rating: Pulse width limited by maximum junction temperature.

2. Surface Mounted on FR4 Board, t ≤ 10 sec.







3. Pulse Test: Pulse width≤300μs, duty cycle≤2%



PJM13P40PA

P-Channel Enhancement Mode Power MOSFET




Typical Characteristic Curves





PJM13P40PA

P-Channel Enhancement Mode Power MOSFET






PJM13P40PA

P-Channel Enhancement Mode Power MOSFET

Package Outline

SOP-8

Dimensions in mm



Ordering Information

Device	Package	Shipping
PJM13P40PA	SOP-8	4,000PCS/Reel&13inches