



Straight Blade Devices

Accessories

For 15 and 20 Ampere, 125 and 250 Volts and 277 Volts AC Devices



NP8



NP26I



SS7

Wallplates, 1-Gang

Description	Color	Duplex Receptacles		Style Line® Receptacles	Single Receptacles with Face Dia. 1.40 in. (35.6)
		Catalog Number	Catalog Number	Catalog Number	Catalog Number
Nylon, smooth.	Almond	NP8AL	NP26AL	NP7AL	
	Black	NP8BK	NP26BK	NP7BK	
	Brown	NP8	NP26	NP7	
	Gray	NP8GY	NP26GY	NP7GY	
	Ivory	NP8I	NP26I	NP7I	
	Light Almond	NP8LA	NP26LA	NP7LA	
	Office White	NP8OW	NP26OW	NP7OW	
	Orange	NP8OR	-	-	
	Red	NP8R	NP26R	NP7R	
	White	NP8W	NP26W	NP7W	
	Stainless steel 302/304, .035 in. (0.9) horizontal brushed finish.		SS8	SS26	SS7
Brass .04 in. (1.0), horizontal brushed finish.		SB8	SB26	SB7	
Aluminum .05 in. (1.3), horizontal brushed finish.		SA8	-	SA7	



HBL52CM22



HBL5206WO



HBL7423WO

Weatherproof Covers

Description	Duplex Receptacles	Single Receptacles with Face Dia. 1.40 in. (35.6)
	Catalog Number	Catalog Number
RTP, gray, for FS/FD box mounting.	HBL5221	HBL7423WO
RTP, yellow, for FS/FD box mounting.	HBL52CM21	HBL74CM23WO
RTP, gray, for device mounting.	HBL5222	-
RTP, yellow, for device mounting.	HBL52CM22	-
Cast aluminum for FS/FD box mounting.	HBL5206WO	HBL7420
Cast aluminum for device mounting.	HBL5205WO	-

Note: All weatherproof plates are UL Listed for Wet Locations.
 Those with suffix WO are listed for use with cover open, all others with cover closed.
 RTP is an abbreviation for reinforced thermoplastic polyester.
 See Section K for more details on cover plates.