



FEMALE

A04	A05	A08	D04	B05

NOTE:

<b>MATERIAL</b>	
M12 INSULATOR	PA66, UL94V-0, BLACK
SPLITTER HOUSING	PVC, UL94V-0, BLACK
CONTACT	GOLD FLASH PLATED BRASS
NUT	NICKEL PLATED BRASS
<b>ELECTRICAL</b>	
RATED CURRENT	2A(8P) / 4A(4/5P)
VOLTAGE	30V(8P) / 60V(5P) / 250V(4P)
INSULATOR RESISTANCE	100 MOhms MIN.
CONTACT RESISTANCE	10 mOhms MAX.
MATING CYCLES	100 CYCLES MIN
<b>ENVIRONMENT</b>	
OPERATION TEMPERATURE	-40°C TO +85°C
IP RATING	IP67 (UNCOUPLED & COUPLED)
<b>RECOMMENDED TORQUE</b>	0.4Nm TO 0.8Nm

**T58-YYY-FFFR001**

SERIES	T58 = M12 T-SPLIT ADAPTER
CONTACT ARRANGEMENT	A04 = (3X) 4P A-CODE A05 = (3X) 5P A-CODE A08 = (3X) 8P A-CODE D04 = (3X) 4P D-CODE B05 = (3X) 5P B-CODE
GENDER	FFF = FEMALE / FEMALE / FEMALE
CONTACT PLATING	1 = GOLD FLASH

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: J. KADEL  
DATE: 12/20/2021

TOLERANCES  
.x ±0.5  
.xx ±0.2  
ANGULAR ±1°

UNITS = mm DO NOT SCALE FROM DRAWING

<b>NorComp</b>	SCALE: NTS	SHEET 1 OF 1	REV 2
	DWG NO. T58-YYY-FFFR001		