




GLASS PASSIVATED SURFACE MOUNT BRIDGE RECTIFIERS

Features

- ◆ Glass Passivated Chip Junction
- ◆ Reverse Voltage - 800 to 1000 V
- ◆ Forward Current- 6.0 A
- ◆ High Surge Current Capability
- ◆ Designed for Surface Mount Application

TTF


Mechanical Data

Case': JEDEC TTF molded plastic body

Terminals': Solderable per MIL-STD-750, Method 2026A

Polarity': Polarity symbol marking on body Mounting

Position': Any

Weight : 0.0163 ounce, 0.461 grams

Dimensions in inches and (millimeters)

Maximum Ratings And Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

Parameter	Symbols	MDD TT6KF	MDD TT6MF	Units
Marking Code				
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	800	1000	V
Maximum RMS voltage	V _{RMS}	560	700	V
Maximum DC Blocking Voltage	V _{DC}	800	1000	V
Maximum Average Forward Rectified Current	I ₀	6		A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	I _{FSM}	200		A
I ² t Rating for Fusing	I ² t	166		A ² S
Maximum Forward Voltage at 1.0 A	V _F	0.83 typ.		V
Maximum Forward Voltage at 6.0 A	V _F	1.0		V
Maximum DC Reverse Current @T _a =25 °C at Rated DC Blocking Voltage @T _a =125 °C	I _R	5 100		µA
Typical Junction Capacitance (Note1)	C _j	60		pF
Typical Thermal Resistance (Note2)	R _{θJA} R _{θJC} R _{θJL}	60 10 12		°C/W
Operating and Storage Temperature Range	T _j , T _{stg}	-55 ~ +150		°C

Note: 1. Measured at 1MHz and applied reverse voltage of 4 V D.C.

2. P.C.B. mounted with 4×1.5"×1.5" (3.81×3.81 cm) copper pad areas.

Typical Characteristics

Fig.1 Average Rectified Output Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Instantaneous Forward Characteristics




Fig.4 Typical Junction Capacitance




Fig.5 Maximum Non-Repetitive Peak Forward Surge Current






Fig.6- Typical Transient Thermal Impedance



The curve above is for reference only.

Suggested Pad Layout

**Note:**

1. Controlling dimension: in/millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

Unit: $\frac{\text{mm}}{(\text{mil})}$