

#### Part Number : 1731120432

Product Description : FCT Stamped Contact, Female, Crimp, 0.10µm Gold Mating Plating, Split Tine, 24-20 AWG, 10 strips of 25 pieces Series Number : 173112 Status : Active Product Category : D-Sub Contacts Engineering Number : S7L



## **Product Environment Compliance**

#### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | ®   |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21                   |
| REACH SVHC         | Not Contained per D(2023)8585-DC<br>(23 Jan 2024) |
| EU RoHS            | Compliant per EU 2015/863                         |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

### **Part Details**

#### General

| Status         | Active   |
|----------------|--|
| Category       | D-Sub Contacts   |
| Series         | 173112   |
| Description    | FCT Stamped Contact, Female,<br>Crimp, 0.10µm Gold Mating Plating,<br>Split Tine, 24-20 AWG, 10 strips of<br>25 pieces |
| Comments       | Packaging Detail: 10 strips of 25 pieces in a box  |
| Contact Type   | Stamped Crimp  |
| Magnetic       | Yes  |
| Product Family | FCT D-Sub Connectors   |
| Product Name   | FCT Products   |
| Туре           | Standard Density   |
| UPC            | 191128226226   |

### Electrical

| Current - Maximum per Contact | 5.0A |
|-------------------------------|------|
|-------------------------------|------|

# Physical

| Durability (mating cycles max) | 50               |
|--------------------------------|------------------|
| Gender                         | Female           |
| Material - Contact             | Copper Alloy     |
| Material - Plating Mating      | Gold over Nickel |
| Net Weight                     | 0.100/g          |
| Orientation                    | Straight         |
| Packaging Type                 | Carton           |
| Plating min - Mating           | 0.100µm          |
| Temperature Range - Operating  | -55° to +125°C   |
| Termination Style              | Crimp            |
| Wire Size (AWG)                | 20, 22, 24       |

Use with Part(s)

| Description | Part Number |
|-------------|-------------|
|-------------|-------------|

This document was generated on Sep 20, 2024