

1332081

https://www.phoenixcontact.com/us/products/1332081

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HDMI cable, degree of protection: IP20, cable length: 1.5 m, number of positions: 19, material: LCP, HDMI High Speed

Your advantages

- · HDMI high-speed patch cables
- · Integrated network transmission thanks to HDMI Ethernet channel
- · Reliable transmission of 4K videos

Commercial data

Item number	1332081
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB14
Product key	ABNEBA
GTIN	4063151628970
Weight per piece (including packing)	100.7 g
Weight per piece (excluding packing)	100.7 g
Customs tariff number	85444290
Country of origin	CN



1332081

https://www.phoenixcontact.com/us/products/1332081

Technical data

Product properties

Product type	Data cable preassembled
Sensor type	HDMI High Speed
Number of positions	19
Shielded	yes
Data management status	
Article revision	00

Electrical properties

Insulation resistance	100 ΜΩ
Test voltage	500 V AC
Test voltage Core/Core	500 V AC
Test voltage Core/Shield	500.00 V AC
Wave impedance	100 Ω

Mechanical properties

Mechanical data

	Insertion/withdrawal cycles	> 10000
--	-----------------------------	---------

Material specifications

Color of the housing part	black
Flammability rating according to UL 94	UL94 V0
Housing material	LCP

Dimensions

Width	20.3 mm
Height	12 mm
Length	49.3 mm

Connector

Connection 1

Туре	Plug straight HDMI type A
Shielded	yes
Insertion/withdrawal cycles	> 10000
Insulation resistance	100 ΜΩ
Degree of protection	IP20

Connection 2

Туре	Plug straight HDMI type A
Degree of protection	IP20



1332081

https://www.phoenixcontact.com/us/products/1332081

Cable/line

Cable length	1.50 m
NO LIBRALL.	
VC HDMI high speed black [HDMI]	
Shielded	yes
UL AWM Style	20276
Cable type	PVC HDMI high speed black
Cable type (abbreviation)	НОМІ
External cable diameter	6.00 mm
Outer sheath, material	PVC
External sheath, color	black
Shielding	Aluminum-lined foil

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C 85 °C
Ambient temperature (storage/transport)	-40 °C 85 °C



1332081

https://www.phoenixcontact.com/us/products/1332081

Classifications

ECLASS

UNSPSC 21.0

ECLASS-11.0	27061801
ECLASS-12.0	27061801
ECLASS-13.0	27060308
ETIM	
ETIM 9.0	EC001262
UNSPSC	

39121400



1332081

https://www.phoenixcontact.com/us/products/1332081

Environmental product compliance

EU RoHS

Yes, No exemptions
EFUP-E
No hazardous substances above the limits
No substance above 0.1 wt%

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com