

Coaxial Cable Connector 16_QN-50-7-5/133_N

Description

Right angle cable plug

QuickLock Interface



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	11 GHz

Mechanical Data

Centre contact	soldered
Outer contact	crimped
Weight	0.0363 kg

Environmental Data

Operating temperature	-40 °C to 125 °C
2011/65/EU (RoHS)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	EPDM (Ethylene propylene diene rubber)	
Crimp ferrule	Copper	

Related Documents

Outline drawing	DOU-00080063
Assembly instruction	DOC-0000181011

Ordering Information

Bulk 100 pcs package	16_QN-50-7-5/133_NH
Single package	16_QN-50-7-5/133_NE

Additional Information

Suitable cables	S_07272_B-05, SPUMA_400-FR, SPUMA_400-UF, LMR-400
Interface standards	QN QLF compliant

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[16_QN-50-7-5/133_NE](#) [16_QN-50-7-5/133_NH](#)