THIS DOCUMENT IS THE PROPERTY OF KEYSTONE ELECTRONICS CORP. AND SHALL NOT BE REPRODUCED, DISTRIBUTED OR USED AS A BASIS FOR MANUFACTURE WITHOUT PRIOR WRITTEN PERMISSION FROM KEYSTONE ELECTRONICS CORP.  $\pm .015 [\pm 0.38]$ 5.187 [131.75] - $\pm .015 [\pm 0.38]$  $\pm .010 [\pm 0.25]$ .187 [4.75] — 4.812 [122.22] -.437 [11.10] TYP. .437 [11.10] TYP. Ø.143 [Ø3.63] HOLE (2) PLS  $\pm .010 [\pm 0.25]$ .625 [15.88] **SCREW CAPTIVATED** 468 [11.89] **BASE** REF. **SCREW TERMINAL** (10) PLS NOTES: 1 BASE BASE: MAT'L .062 [1.57]TH'K G10 UL 94V-0 2. TERMINAL: P/N 1248 MAT'L: .032 [0.81] TH'K STEEL, TIN PLATE SCREW: 6-32 THREAD MAT'L: STEEL, NICKEL PLATE KEYSTONE ELECTRONICS CORP. www.keyelco.com • NEW HYDE PARK NY 11040 • Tel (516)328-7500 PART NAME STANDARD BINDING POST STRIP MATERIAL AS NOTED FINISH DRN BY **BOONE** 10.10.01 AS NOTED APP'D BASE MAT'L WAS GPO-3 FIBERGLASS RH 1X 4.20.23 CHANGE AS PER ECN 23-060 Α INCH [MM] CODE TOLERANCES DWG NO.  $\pm .005 [\pm 0.13]$ DECIMAL 4176 C ANGULAR ± 1° DATE **DESCRIPTION** REV. UNLESS OTHERWISE SPECIFIED