2203543

https://www.phoenixcontact.com/us/products/2203543



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Graphic LCD module, 2.8", 128 x 64 pixels, FSTN transflective/positive 6:00, LED backlight, interface: 8 bit, operating temperature: -20 $^\circ C$... 70 $^\circ C$



Your advantages

- Graphic LCD module
- · Easy and time-saving integration into HCS series electronics housings
- · Long-term availability
- · Ideal protective shield and gasket material
- · Backlighting can be switched on and off
- · Common interface for your electronics

Commercial data

Item number	2203543
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AC05
Product key	ACGAAA
GTIN	4055626481975
Weight per piece (including packing)	56.2 g
Weight per piece (excluding packing)	26 g
Customs tariff number	85299020
Country of origin	DE

2203543

https://www.phoenixcontact.com/us/products/2203543



Technical data

Notes

General	The background color may vary slightly depending on the ambient temperature. This procedure can be reversed.
Notes on safety	NOTE: Electrostatic discharge! The device contains components that can be damaged or destroyed by electrostatic discharge. When handling the device, observe the necessary safety precautions against electrostatic discharge (ESD) according to EN 61340-5-1 and IEC 61340-5-1.
Product properties	
Product type	Display
Data management status	
Article revision	01
Display	
Display type	Graphic LCD module
Display type	LCD with backlighting
Diaplay tupa	tranomiacius

Product type	Display
ata management status	
Article revision	01
isplay	
Display type	Graphic LCD module
Display type	LCD with backlighting
Display type	transmissive
Panel technology	FSTN
Diagonals (cm)	7.11 cm
Diagonals (inch)	2.8 in.
Screen resolution	128 x 64 Pixel(s)
Display lighting type	LED, white
Contrast ratio	4
Viewing direction	6:00
Controller	NT7538
Representation	positive

Interfaces

	Interface	8-bit parallel
Dim	nensions	
	Dimensions	70 mm x 49 mm x 5 mm (Mounting panel dimensions)
		63 mm x 35 mm (Viewing area)
		60 mm x 30 mm (Active range)
Mat	terial specifications	

untreated

Environmental	and	roal_lifo	conditions
Environmental	anu	real-life	CONTINUOUS

Surface characteristics

Vibration test	
Specification	IEC 60068-2-6:2007-12

2203543

https://www.phoenixcontact.com/us/products/2203543



Frequency	10 - 55 - 10 Hz	
Sweep speed	1 octave/min	
Test duration per axis	15 min.	
Test directions	X-, Y- and Z-axis	
Ambient conditions		
Ambient temperature (operation)	-20 °C 70 °C	
Ambient temperature (storage/transport)	-30 °C 80 °C	
Relative humidity (storage/transport)	93 %	
Mounting		
Mounting type	Screw mounting	
Packaging specifications		
Type of packaging	packed in cardboard	

2203543

https://www.phoenixcontact.com/us/products/2203543



Classifications

ECLASS

ECLASS-12.0 27261890	ECLASS-11.0	27261890
ECLASS-13.0 27261890	ECLASS-12.0	27261890
	ECLASS-13.0	27261890

ETIM

	ETIM 9.0	EC011541		
UN	UNSPSC			
	UNSPSC 21.0	43211900		

2203543 https://www.phoenixcontact.com/us/products/2203543



Accessories

HCS-C MINI 1W C C C 7035 - Electronics housing

2203147 https://www.phoenixcontact.com/us/products/2203147



Handheld housing, C-Mini, light gray, consisting of two half shells with screws, front 1.1 mm recessed with window and keypad slot

HCS-C MINI 1W 9V 1 C 7035 - Electronics housing

2203150

https://www.phoenixcontact.com/us/products/2203150



Handheld housing, C-Mini, light gray, consisting of two half shells, front plate above, screws. Front 1.1 mm recessed, with window and keypad slot, battery compartment cover and battery contacts for 9 V battery

2203543 https://www.phoenixcontact.com/us/products/2203543



HCS-C MINI 1W 3AAA 1 1 7035 - Electronics housing

2203152

https://www.phoenixcontact.com/us/products/2203152



Handheld housing, C-Mini, light gray, consisting of two half shells, two front plates, screws. Front 1.1 mm recessed, with window and keypad slot, battery compartment cover and battery contacts for 3 AA batteries

HCS-C MINI-P 1W C C C 7035 - Electronics housing

2203153

https://www.phoenixcontact.com/us/products/2203153



Handheld housing, C-Mini-Plus, light gray, consisting of two half shells with screws, front 1.1 mm recessed, with window and keypad slot

2203543 https://www.phoenixcontact.com/us/products/2203543



HCS-C MINI-P 1W C 1 1 7035 - Electronics housing

2203155

https://www.phoenixcontact.com/us/products/2203155



Handheld housing, C-Mini-Plus, light gray, consisting of two half shells, two front plates with screws, front 1.1 mm recessed, with window and keypad slot

HCS-C MEDIUM 1W C 1 C 7035 - Electronics housing

2203162

https://www.phoenixcontact.com/us/products/2203162



Handheld housing, C-Medium, light gray, consisting of two half shells, front plates above with screws, front 1.1 mm recessed, with window and keypad slot

2203543 https://www.phoenixcontact.com/us/products/2203543



HCS-C MEDIUM 1W 3AA 1 1 7035 - Electronics housing

2203163

https://www.phoenixcontact.com/us/products/2203163



Handheld housing, C-Medium, light gray, consisting of two half shells, two front plates, screws. Front 1.1 mm recessed, with window and keypad slot, battery compartment cover and battery contacts for 3 AA batteries

HCS-T MINI 1W C C C 7035 - Electronics housing

2203131 https://www.phoenixcontact.com/us/products/2203131



Handheld housing, T-Mini, light gray, consisting of two half shells with screws, front 1.1 mm recessed, with window and keypad slot

2203543 https://www.phoenixcontact.com/us/products/2203543



HCS-T MINI 1W 3AA C C 7035 - Electronics housing

2203134

https://www.phoenixcontact.com/us/products/2203134



Handheld housing, T-Mini, light gray, consisting of two half shells with screws. Front 1.1 mm recessed, with window and keypad slot, battery compartment cover and battery contacts for 3 AA batteries

HCS-C MAXI 1W C C C 7035 - Electronics housing

2203166

https://www.phoenixcontact.com/us/products/2203166



Handheld housing, C-Maxi, light gray, consisting of two half shells with screws, front 1.1 mm recessed with window and keypad slot

2203543 https://www.phoenixcontact.com/us/products/2203543



HCS-C MAXI 1W C 1 1 7035 - Electronics housing

2203167

https://www.phoenixcontact.com/us/products/2203167



Handheld housing, C-Maxi, light gray, consisting of two half shells, two front plates with screws, front 1.1 mm recessed, with window and keypad slot

HCS-C MAXI 1W 2X3AA 1 1 7035 - Electronics housing

2203168

https://www.phoenixcontact.com/us/products/2203168



Handheld housing, C-Maxi, light gray, consisting of two half shells, two front plates, screws. Front 1.1 mm recessed, with window and keypad slot, battery compartment cover and battery contacts for 6 AA batteries

2203543 https://www.phoenixcontact.com/us/products/2203543



HCS-C MAXI 1W 2X9V 1 1 7035 - Electronics housing

2203170

https://www.phoenixcontact.com/us/products/2203170



Handheld housing, C-Maxi, light gray, consisting of two half shells, two front plates, screws. Front 1.1 mm recessed, with window and keypad slot, battery compartment cover and battery contacts for 2x 9 V battery

HCS-T MEDIUM 1W C 1 1 7035 - Electronics housing

2203138

https://www.phoenixcontact.com/us/products/2203138



Handheld housing, T-Medium, light gray, consisting of two half shells, two front plates with screws, front 1.1 mm recessed, with window and keypad slot

2203543 https://www.phoenixcontact.com/us/products/2203543



HCS-T MEDIUM 1W C C 1 7035 - Electronics housing

2203139

https://www.phoenixcontact.com/us/products/2203139



Handheld housing, T-Medium, light gray, consisting of two half shells, front plates below with screws, front 1.1 mm recessed, with window and keypad slot

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com