



SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000 MΩ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material:Nylon66, UL94V-0

| 编 号 | 尺寸 (mm) | |
|-------------|---------|-------|
| | A | B |
| XH25401-02Y | 2.50 | 7.50 |
| XH25401-03Y | 5.00 | 10.00 |
| XH25401-04Y | 7.50 | 12.50 |
| XH25401-05Y | 10.00 | 15.00 |
| XH25401-06Y | 12.50 | 17.50 |
| XH25401-07Y | 15.00 | 20.00 |
| XH25401-08Y | 17.50 | 22.50 |
| XH25401-09Y | 20.00 | 25.00 |
| XH25401-10Y | 22.50 | 27.50 |
| XH25401-11Y | 25.00 | 30.00 |
| XH25401-12Y | 27.50 | 32.50 |
| XH25401-20Y | 47.50 | 52.50 |

| | | | | | | | | | | | | | | | | |
|-------------|---------------------|------------|-------------------|------------|---------------|-------------|----------------|----------------|--------------|-------------|------------|-------------|-------------------|----|-------------|-----|
| 制图 DRAWN | 变更内容 DESCRIPTION | 日期 DATE | GENERAL TOLERANCE | | 制图 DRAWING | 黄彬 | | 料号 PART NO. | HX XH2.54-8Y | | 版本 REV. | A | | | | |
| | | | X.±0.25 | X.*±2' | | 审核 CHECK | 张伟 | | 品名 TITLE | 压线端子胶壳 | | 页次 SHEET | 1/1 | | | |
| | | | .XX±0.20 | .X'±1' | | | 核准 APPROVAL | | | 罗小春 | | | 客户料号 CUTM. NO. | | | |
| | | | .XX±0.15 | .XX'±0.5' | | | | | | 单位 UNITS | | | | MM | 比例 SCALE | 1:1 |
| | | | .XXX±0.10 | .XXX'±0.5' | | | | | | | | | | | | |