

1785430

https://www.phoenixcontact.com/us/products/1785430

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Protective cap, Range of articles: SUNCLIX, color: black, self-sealing, without interlock, set consisting of: 1 protective cap for connector side and 1 protective cap for coupling side



#### Commercial data

Item number	1785430
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	AB02
Product key	ABLBZC
Catalog page	Page 420 (C-2-2013)
GTIN	4046356569613
Weight per piece (including packing)	4.078 g
Weight per piece (excluding packing)	4.042 g
Customs tariff number	39269097
Country of origin	DE



1785430

https://www.phoenixcontact.com/us/products/1785430

### Technical data

#### Notes

es	
General	self-sealing, without interlock, set consisting of: 1 protective cap for connector side and 1 protective cap for coupling side (Unplugged connectors can be sealed for transportation and maintenance with the IP65/67 protective cap.)
afety note	
Safety note	<ul> <li>WARNING: Commission properly functioning products only.</li> <li>The products must be regularly inspected for damage.</li> <li>Decommission defective products immediately. Replace damaged products. Repairs are not possible.</li> </ul>
	<ul> <li>WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.</li> </ul>
	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
	<ul> <li>The products are suitable for applications in plant, controller, and electrical device engineering.</li> </ul>
	<ul> <li>Assembled products may not be manipulated or improperly opened.</li> </ul>
	<ul> <li>Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).</li> </ul>
	<ul> <li>When using the product in direct connection with third-party manufacturers, the user is responsible.</li> </ul>
	<ul> <li>For operating voltages &gt; 50 V AC, conductive connector housings must be grounded</li> </ul>
	<ul> <li>Ensure that the protective or functional ground has been properly connected.</li> </ul>
	Observe the corresponding technical data. You will find information: On the product On the packing label In the supplied documentation Online at phoenixcontact.com/products under the product
	<ul> <li>The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.</li> </ul>
	<ul> <li>Use a protective cap to protect connectors that are not in use.</li> <li>The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products</li> </ul>
	<ul> <li>The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting</li> </ul>

warnings (e.g. DIN EN ISO 13732-1:2008-12).

• Operate the connector only when it is fully plugged in and



1785430

https://www.phoenixcontact.com/us/products/1785430

	interlocked.
	<ul> <li>Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.</li> </ul>
	<ul> <li>Observe the minimum bending radius of the cable. Lay the cable without twisting it.</li> </ul>
roduct properties	
Product type	Photovoltaic connector
Product family	SUNCLIX
Pitch	0 mm
Data management status	
Article revision	00
mensions	
Width	19 mm
Height	23.3 mm
Length	59 mm
Pitch	0 mm
aterial specifications	
Color	black
Insulating material	TPE
nvironmental and real-life conditions  Ambient conditions	
Degree of protection	IP65/IP67 (see also the description in the connector installation manuals)
Ambient temperature (operation)	-40 °C 85 °C



1785430

https://www.phoenixcontact.com/us/products/1785430

### Classifications

#### **ECLASS**

	ECLASS-11.0	27440208		
	ECLASS-12.0	27440208		
	ECLASS-13.0	27440208		
ETIM				
	ETIM 9.0	EC002314		
UNSPSC				
	UNSPSC 21.0	39121400		



1785430

https://www.phoenixcontact.com/us/products/1785430

### Environmental product compliance

#### EU RoHS

20 1.01.0			
Fulfills EU RoHS substance requirements	Yes, No exemptions		
China RoHS			
Environment friendly use period (EFUP)	EFUP-E		
	No hazardous substances above the limits		
EU REACH SVHC			
REACH candidate substance (CAS No.)	No substance above 0.1 wt%		

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com