

### CGS | CGS HCH

TE Internal #: 2176465-8

Power Resistor, 220 ohm, 400 W, Wire Wound, 2 Termination, ±200


ppm/°C, .05 %, Flying Leads Termination, Loose Piece - Box, 1

Resistor, CGS HCH

View on TE.com >



Passive Components > Resistors > Chassis Mount Resistors > Aluminium Housed Braking Resistor: IP54, 200W~500W Power - HCH Series



Resistor Type: Power Resistor Resistance Class: Up to  $1k\Omega$  Resistance Value:  $220 \Omega$  Power Rating: 400 W

Element Type: Wire Wound

All Aluminium Housed Braking Resistor: IP54, 200W~500W Power - HCH Series (34)

### **Features**

### **Product Type Features**

Chassis Mount Resistor Termination Type

Resistor Type	Power Resistor
Element Type	Wire Wound
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Resistance Class	Up to 1kΩ
Resistance Value	220 Ω
Power Rating	400 W
Passive Component Tolerance	.05 %
Termination Features	
Number of Terminations	2

Flying Leads



#### Mechanical Attachment

Panel Mount Feature Type	Flange with Mounting Holes
Dimensions	
Product Height	31 mm[1.22 in]
Product Length	265 mm[10.433 in]
Product Width	60 mm[2.362 in]
Usage Conditions	
Temperature Coefficient	±200 ppm/°C
Packaging Features	
Packaging Method	Loose Piece - Box

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Hand solderable with lead free solder

#### Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





## Also in the Series | CGS HCH



# Customers Also Bought







### **Documents**

**Product Drawings** 

HCH265 400W 220R 5% LEAD

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2176465-8\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2176465-8\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2176465-8\_A.3d\_stp.zip

Power Resistor, 220 ohm, 400 W, Wire Wound, 2 Termination, ±200 ppm/°C, .05 %, Flying Leads Termination, Loose Piece - Box, 1 Resistor, CGS HCH



English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Aluminium Housed Braking Resistor Type HCH Series

English