

https://www.phoenixcontact.com/us/products/1033482

1033482



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Rogowski coil, The Rogowski coil measures the AC current of rails and power lines.



#### Commercial data

Item number	1033482
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C444
Product key	CK4A12
Catalog page	Page 219 (C-5-2019)
GTIN	4055626539041
Weight per piece (including packing)	385.6 g
Weight per piece (excluding packing)	372.4 g
Customs tariff number	90309000
Country of origin	DE



https://www.phoenixcontact.com/us/products/1033482



### Technical data

#### Product properties

Product type	Rogowski coil
Set comprises	1033483 PACT RCP-4000A-1A-D140-10M
Data management status	
Article revision	03
Insulation characteristics	
Pollution degree	2

#### Electrical properties

#### Measuring coil

Conductor structure signal line	2x 0.22 mm (Signal (tinned))
	1x 0.22 mm (Shielding (tinned))
Insulation	double insulation
Rated insulation voltage	1000 V AC (rms CAT III)
	600 V AC (rms CAT IV)
Test voltage	10.45 kV DC (60 s)
Basic accuracy	<± 0.2 %

#### General

Converter type	Rogowski coil
----------------	---------------

#### Input data

#### Frequency

Designation	Measuring coil
Frequency measuring range	40 Hz 20000 Hz
Position error	<± 0.1 % (typical)
Linearity error	< 0.1 %

#### Current transformer

Converter type	Rogowski coil

#### Output data

#### Signal

<u> </u>	
Designation	Measuring coil
Output signal (at 50 Hz)	100 mV (no load, at 1,000 A)
Output voltage (in no-load operation)	V <sub>OUT</sub> = M * dl/dt
Output voltage (sinusoidal, in no-load operation)	100 mV ( $V_{OUT}$ = 2 * $\pi$ * M * f * I (M = 0.318 $\mu$ H; example: At 50 Hz; I = 1,000 A))

#### Dimensions



https://www.phoenixcontact.com/us/products/1033482



Meas	surina	COIL

Length	450 mm
Diameter	8.3 mm ±0.2 mm
Measuring coil when installed	
Diameter	140 mm
Signal line	
Length	10 m

#### Material specifications

Housing material	PC
Coil material	Elastollan

#### Environmental and real-life conditions

#### Ambient conditions

Measuring coil degree of protection	IP54 (not assessed by UL)
Ambient temperature (operation)	-30 °C 80 °C (Measuring coil)
Ambient temperature (storage/transport)	-40 °C 80 °C (Measuring coil)
Altitude	< 2000 m
Permissible humidity (operation)	5 % 95 % (non-condensing)

### Approvals

11	ıv	$\sim$	^
u	ı۲\	·	_

Certificate	UKCA-compliant		
CMIM			
Certificate	CMIM-compliant		
UL, USA/Canada			
Identification	UL 61010 Recognized		
Note	Measuring coil		

### Standards and regulations

Standards/regulations	IEC 61010-1
	IEC 61010-2-030
	IEC 61869-10

### Mounting

Thread type	()



1033482

https://www.phoenixcontact.com/us/products/1033482

### **Approvals**

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1033482



cUL Recognized

Approval ID: FILE E 357804



**UL Recognized**Approval ID: FILE E 357804



EAC

Approval ID: RU\*DE\*08.B.01187/19

cULus Recognized



https://www.phoenixcontact.com/us/products/1033482



### Classifications

#### **ECLASS**

	ECLASS-11.0	27210992		
	ECLASS-12.0	27210992		
	ECLASS-13.0	27210992		
ETIM				
	TIVI			
	ETIM 9.0	EC002498		
UNSPSC				
	UNSPSC 21.0	39121000		



https://www.phoenixcontact.com/us/products/1033482



### Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions		
China RoHS			
Environment friendly use period (EFUP)	EFUP-E		
	No hazardous substances above the limits		
EU REACH SVHC			
REACH candidate substance (CAS No.)	No substance above 0.1 wt%		

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com