



TE Connectivity: Every Connection Counts
© 2015 TE Connectivity Ltd. family of companies. All Rights Reserved

+ CONNECTORS

POWER CONTACTS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

III+ PIN,24-20,TIN-LEAD,SMPACK

AMP | Type III+

66400-6

TE Internal Number: 66400-6

Not EU RoHS Compliant

Not EU ELV Compliant

Product Type **Contact**

Wire/Cable Size (AWG) **24 – 20**

Wire/Cable Size (mm²) **.2 – .6**

Circuit Application **Signal**

Applies To **Wire/Cable**

Product Drawings

PIN ASSEMBLY, LOOSE PIECE, TYPE

PDF

English

CAD Files

Customer View Model

2D_DXF.ZIP

English

3D PDF

PDF

3D

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

Instruction Sheets

Instruction Sheet (U.S.)

Selection Of Multimate Pin And Socket Contacts

PDF

English

Selection Of Multimate Pin And Socket Contacts





PDF

Japanese

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Contact
Electrical Characteristics	Test Current (A)	13
Contact Features	Contact Type	Pin
	Contact Base Material	Brass
	Contact Mating Area Plating Material	Tin-Lead
	Contact Mating Area Plating Finish	Bright
	Contact Termination Area Plating Material	Tin-Lead
	Contact Termination Area Plating Finish	Bright
	Contact Size	16
Termination Features	Wire/Cable Size (AWG)	24 – 20
	Wire/Cable Size (mm ²)	.2 – .6
	Termination Type	Crimp
Dimensions	Accepts Wire Insulation Diameter Range	2.03 – 2.54 mm [.08 – .1 in]
Operation/Application	Circuit Application	Signal
	Applies To	Wire/Cable
Packaging Features	Packaging Method	Box, Loose Piece
Other	Comment	Overall insulation crimp diameter, including crimp barrel, must not exceed 3.18 [.125].
	For Use With	CPC Connectors
	Wire/Cable Type	Discrete Wire
Statement of Compliance	Statement of Compliance PDF	

Customers Also Bought

<p>TO-5/.100 GRID RELAYS</p>  <p>J1MAC-5XM = M39016/7-025M J1MAC-5XM</p>	<p>SWITCH KNOBS</p>  <p>KPN700B1/4=KNOB BLK W/POINTER KPN700B1/4</p>	<p>POWER CONTACTS</p>  <p>III+ SKT, 24-20, TIN-LEAD, SMPACK 66399-6</p>	<p>POWER CONTACTS</p>  <p>III+ SOC, SOLTAB, TIN-LEAD, LP 202237-2</p>
--	--	--	---