

Part Number: 464369312

Product Description: EXTreme Ten60Power Right-Angle Receptacle with Side Guides, 2 DC Power Circuits, 15 Signal Circuits, Press Fit Tail

Series Number: 46436

Status: Active

Product Category: Board-to-Board

Connectors



Documents & Resources

Drawings

464369312_sd.pdf 464361001-PK-000.pdf

3D Models and Design Files

464369312_stp.zip

Specifications

<u>PS-46436-100-001.pdf</u> 464361000-TS-000.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Compliant with Exemption 44; 34; 33 |
|--------------------|--|
| China RoHS | @ |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|--|
| Category | Board-to-Board Connectors |
| Series | 46436 |
| Description | EXTreme Ten60Power Right-Angle Receptacle with Side Guides, 2 DC Power Circuits, 15 Signal Circuits, Press Fit Tail |
| Application | Board-to-Board, Power, Signal |
| Comments | See Product Specification for details |
| Component Type | PCB Receptacle |
| Keyword | Ten60 |
| Product Name | EXTreme Ten60Power |
| UPC | 195842670693 |

Agency

| CSA | LR19980 |
|-----|---------|
| UL | E29179 |

Electrical

| Current - Maximum per Contact | 60.0A |
|-------------------------------|-------------------|
| Grounding to PCB | No |
| Voltage - Maximum | 600V AC / 250V DC |

Physical

| Circuits (Loaded) | 17 |
|--------------------|-------|
| Circuits (maximum) | 17 |
| Color - Resin | Black |

| Durability (mating cycles max) | 200 |
|--------------------------------|------------------------------|
| Flammability | 94V-0 |
| Glow-Wire Capable | No |
| Guide to Mating Part | Side, Yes |
| Keying to Mating Part | None |
| Lock to Mating Part | No |
| Mated Height | 10.00mm |
| Material - Metal | High Conductivity Copper |
| Material - Plating Mating | Gold |
| Material - Plating Termination | Tin |
| Material - Resin | Liquid Crystal Polymer |
| Net Weight | 11.956/g |
| Number of Rows | 1, 5 |
| Orientation | Right Angle |
| Packaging Type | Tray |
| PC Tail Length | 2.50mm, 3.28mm |
| PCB Locator | Yes |
| PCB Retention | Yes |
| PCB Thickness - Recommended | 1.58mm |
| Pitch - Mating Interface | 2.00mm, 5.50mm |
| Plating min - Mating | 0.762µm |
| Plating min - Termination | 2.540µm |
| Polarized to Mating Part | Yes |
| Polarized to PCB | Yes |
| (p)ower-(s)ignal Configuration | 2p - 15s |
| Stackable | No |
| Temperature Range - Operating | -40° to +105°C |
| Termination Interface Style | Through Hole - Compliant Pin |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|----------------|---------------|
| 2 2321.194.311 | i di citamber |

EXTreme Ten60Power Right-Angle Plug with Side Guides, 2 DC Power Circuits, 15 Signal Circuits, Press Fit Tail

464379312

This document was generated on Oct 15, 2024