480142-2 × OBSOLETE

AMP-LEAF


TE Internal #: 480142-2

TE Internal Description: HSG AMP LEAF 22 POS

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings



Connector Product Type: Housing

Connector & Housing Type: Receptacle

Connector System: Wire-to-Board

Number of Positions: 22

Centerline (Pitch): 3.96 mm [.156 in]

Features

Product Type Features

Connector Product Type	Housing
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Dual Positions	22
Number of Positions	22
Number of Rows	2

Electrical Characteristics

Operating Voltage	250 VAC
,	

Body Features

Primary Product Color	Black
-----------------------	-------

Contact Features

Contact Type	Socket
Contact Base Material	Phosphor Bronze
Contact Current Rating (Max)	5 A

Termination Features

Mechanical Attachment



Strain Relief	Without
Panel Mount Feature	Without
Panel Mount Feature Type	Mounting Ears
Connector Mounting Type	Board Mount
Housing Features	
Housing Entry Configuration	Both Ends Closed
Housing Material	Diallyl Phthalate
Centerline (Pitch)	3.96 mm[.156 in]
Dimensions	
Connector Length	108.74 mm[4.281 in]
Connector Height	8.89 mm[.35 in]
PCB Thickness (Recommended)	1.4 – 1.78 mm[.055 – .07 in]
Row-to-Row Spacing	4.14 mm[.163 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Glow Wire Rating	Standard Part - Not Glow Wire
Packaging Features	
Packaging Quantity	250
Packaging Method	Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold:



tris(2-methoxyethoxy)vinylsilane (.11% in Component Part)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Not Low Halogen - contains Br or Cl > 900 ppm.

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Customers Also Bought















Documents

Product Drawings
HSG AMP LEAF 22 POS

English

CAD Files

3D PDF



3D

Customer View Model

ENG_CVM_CVM_480142-2_BA.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_480142-2_BA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_480142-2_BA.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of u

Product Specifications

Product Specification

English

Connector, AMP-LEAF, .000030 Gold Plated Contacts, DPH Housing

English

Product Specification

English

Connector, AMP-LEAF, Phenolic or Thermoplastic Housing

English

Product Specification

English

Connector, AMP-LEAF, Tin Plated Contact

English

Instruction Sheets

Instruction Sheet (U.S.)

English

INTER-CONTACT KEYING PLUG NO. 583274-1 FOR AMP-LEAF CONNECTORS

English

Agency Approvals

Agency Approval Document

English