

6 5 4 3 2 1

APPROVED: _____
 DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	5/2/14	

SECTION A-A

SPECIFICATIONS:

Material:
 Insulator: PA66, rated UL 94V-0
 Insulator color: Green
 Wire guard: M3, Steel, Zinc plated
 Clamp: Brass, Nickel plated
 Wire guard: Phosphor Bronze, Nickel plated

Electrical:
 Voltage rated: 300 VAC
 Current rating: 15 Amps
 Contact resistance: 20 mohms max
 Insulation resistance: 500 Mohms min @ 500 VDC
 Dielectric withstanding voltage: 2,000 VAC for 1 minute

Wire range: 28-14 AWG, 2.5mm²
 Torque (lb-in): 4.5
 Wire strip length: 7-8mm
 Temperature Rating:

Operating temperature: -40°C to +105°C
 Environmental:
 Lead free, RoHS compliant.

Positions: 2 thru 24
 A = .200 [5.08] x No. of Positions
 B = .200 [5.08] x No. of Spaces

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE INCHES [MM]
 TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	± .10
.XX	± .020	Ø.XX	± .015
.XXX	± .015	Ø.XXX	± .010

ADAM TECH

909 Rahway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

APPROVALS		DATE
DRAWN	HR	5/2/14
CHECKED	SY	5/2/14
APPROVED		

TITLE		
EURO BLOCK, .200 [5.08] PITCH		
SIZE	PART NO.	REV.
X	EB9A-XX-D	-
REF: S00067C	SCALE: NTS	SHEET 1 OF 1

6 5 4 3 2 1