



**Ordering Information:**

A7921HG-2P - <sup>\*\*\*</sup>/<sub>2</sub> - <sup>\*\*\*</sup>/<sub>3</sub>

1.Part NO.

2.Material:

(Blank): Nylon 66,UL94V-0

GWT: Nylon 66,UL94V-0,IEC 60335-1,5th Edition  
Glow Wire Capable.

3.Color:

(Blank): White

BK: Black

IV: Ivory

**SPECIFICATIONS:**

Current Rating: 10A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 10mΩ Max.

Insulation Resistance: 1000MΩ Min.

Withstanding Voltage: 1500V AC/minute

<b>CJTconn</b> CHANGJIANG CONNECTORS CO.,LTD.			TITLE	
Unit	Scale	Sheet	7.92mm PITCH HOUSING	DRAWING NO. A7921HG-2P
mm	2.5:1	1 of 1		
DRWN	CHK'D	APPR		
Wenmin Luo	DianKui Wan	Jack Yin		REV A0
General Tolerances		THIRD ANGLE PROJECTION		
x.xx±0.25				
x.xxx±0.20				
x.xxxx±0.15				
ANGLES ±1°				

A0	NEW RELEASE	2020.07.01
REV	DESCRIPTION	DATE