EV200HAANA <a>ACTIVE

Kilovac | Kilovac EV200 TE Internal #: 1-1618002-8 12 – 900VDC Contact Voltage, 1 Form X SPST-NO, Stud Terminals Main Connection, Flying Leads Coil Connection, Kilovac EV200, High Voltage Relays

View on TE.com >

Relays & Contactors > Relays > High Voltage Relays



Contact Voltage Rating: 12–900 VDC Contact Arrangement: 1 Form X SPST-NO Coil Termination & Connection Type: Flying Leads Main Termination & Connection Type: Stud Terminals Power Switching: Yes

Features

Configuration Features

Contact Arrangement

Relay Options

connectivity

1 Form X SPST-NO

Not RF Rated

Electrical Characteristics

Contact Voltage Rating	12 – 900 VDC						
Contact Current Rating	500 A						
Coil Voltage Rating	900 VDC						
Coil Resistance	3.14 Ω						
Contact Switching Voltage (Max)	900 VDC						
Contact Features							
Contact Material	Copper						
Termination Features							
Coil Termination & Connection Type	Flying Leads						
Main Termination & Connection Type	Stud Terminals						
Mechanical Attachment							
Product Mounting Feature Type	Flange with Mounting Holes						
Product Mount Type	Chassis						
Operation/Application							

C For support call+1 800 522 6752

EV200HAANA

12 – 900VDC Contact Voltage, 1 Form X SPST-NO, Stud Terminals Main Connection, Flying Leads Coil Connection, Kilovac EV200, High Voltage Relays



Power Switching

Yes

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Hand solderable with lead free solder

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | Kilovac EV200

C For support call+1 800 522 6752

EV200HAANA

12 – 900VDC Contact Voltage, 1 Form X SPST-NO, Stud Terminals Main Connection, Flying Leads Coil Connection, Kilovac EV200, High Voltage Relays





Customers Also Bought



BSMB-35/150	MXSU-3121	HV-BDC 500A/1000V 35H-511-0100-	RT423005
		OR2100001	

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1618002-8_E.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1618002-8_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1618002-8_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

5-1773450-5_sec7_EV200A

English

EV200HAANA

12 – 900VDC Contact Voltage, 1 Form X SPST-NO, Stud Terminals Main Connection, Flying Leads Coil Connection, Kilovac EV200, High Voltage Relays

