Product data sheet Characteristics

ZCKM1H29

Limit switch body, Limit switches XC Standard, ZCKM, 1NC+1 NO, snap action, M20





Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch body
Device short name	ZCKM
Body type	Fixed
Product Compatibility	XCKM
Associated head	ZCKD06 ZCKD16 ZCKD219 ZCKD08 ZCKD21 ZCKD05 ZCKD81 ZCKD23 ZCKD23 ZCKD239 ZCKD10 ZCKD41 ZCKD41 ZCKD15 ZCKD029 ZCKD029 ZCKD59 ZCKD02 ZCKD17 ZCKD109 ZCKD109 ZCKD10
Body Material	Metal
Cable entry	3 entries tapped for M20 x 1.5 cable gland
Number of poles	2
Contacts type and composition	1 NC + 1 NO
Contact operation	Snap action
Number of steps	1 1 position
Contacts material	Silver plated contacts

Complementary

Local display	Without
Electrical connection	Screw-clamp terminals 1 x 0.342 x 1.5 mm ²
Positive opening	With
Minimum actuation speed	0.01 m/min
[le] rated operational current	3 A 240 V, AC-15, A300 EN/IEC 60947-5-1 appendix A 0.27 A 250 V, DC-13, Q300 EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	500 V 3)IEC 60947-1 contact block 300 VCSA C22.2 No 14 contact block 300 VUL 508 contact block
Maximum resistance across terminals	0.25 mOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	6 KV IEC 60664 6 kV IEC 60947-1
Short-circuit protection	10 A cartridge fuse gG
Electrical durability	5000000 Cycles, DC-13 120 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 13 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 9 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C
Width	2.52 in (64 mm)
Height	2.52 in (64 mm)

Depth	1.18 in (30 mm)
Net Weight	0.46 lb(US) (0.21 kg)
Terminals description ISO n°1	(21-22)NC
	(13-14)NO

Environment

IP Degree of Protection	IP66	
IK degree of protection	IK05	
Ambient air temperature for operation	-13158 °F (-2570 °C) standard environment	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Environmental characteristic	Standard environment	

Ordering and shipping details

Category	22416 - LIMIT SWITCHES,IEC,XCKL
Discount Schedule	Т
GTIN	3389110739503
Nbr. of units in pkg.	1
Package weight(Lbs)	7.94 oz (225 g)
Returnability	Yes
Country of origin	ID

Packing Units

r acking office	
Unit Type of Package 1	PCE
Package 1 Height	2.60 in (6.6 cm)
Package 1 width	1.26 in (3.2 cm)
Package 1 Length	3.35 in (8.5 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	640
Package 2 Weight	361.96 lb(US) (164.18 kg)
Package 2 Height	27.56 in (70 cm)
Package 2 width	23.62 in (60 cm)
Package 2 Length	31.50 in (80 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

<u></u>		
Warranty	18 months	