

4		3		2		1					
THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		20							
© COPYRIGHT 20		BY -		ALL RIGHTS RESERVED.							
NOTES: 1. MATERIALS AND FINISH HOUSING: PA 6-6, UL 94-VO, COLOR: GREEN CLAMP: BRASS, NICKEL PLATED. CLAMPING SCREW: M3.5, BRASS, NICKEL PLATED. TERMINAL: BRASS, TIN PLATED. 2. MECHANICAL WIRE STRIPPING LENGTH : 7.0-8.0 mm MIN. PC BOARD HOLES DIAMETER : 1.3 mm MAX. PC BOARD THICKNESS : 4 mm RECOMMENDED TIGHTENING TORQUE FOR SCREW : 0.8 Nm. 3. ELECTRICAL WIRE RANGE : 10-30 AWG MAX. VOLTAGE : 600 V MAX CURRENT : 30 A CONTACT RESISTANCE : <15 m Ohm INSULATION RESISTANCE : >1000 M Ohm (500V DC) 4. END-TO-END STACKABLE W/INTERLOCK, WITHOUT LOSS OF CENTERLINE SPACING. 5. RECOGNIZED UNDER THE COMPONENT PROGRAM OF UNDERWRITERS LABORATORY INC. FILE No. E60677. △6 NOT CUMULATIVE TOLERANCE. 7. PACKED IN TRAY.						REVISIONS					
						P	LTR	DESCRIPTION	DATE	DWN	APVD
							-	SEE SHEET 1	-	-	-
						D					
						C					
						B					
						A					

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±0.15

1 PLC ±0.2

2 PLC ±0.2

3 PLC ±-

4 PLC ±-

ANGLES ±-

FINISH

MATERIAL

SEE NOTES

DWN E. ZANOLINI 06MAR2001

CHK E. ZANOLINI 06MAR2001

APVD D. BIEVENOUR 06MAR2001

PRODUCT SPEC -

APPLICATION SPEC -

WEIGHT -

CUSTOMER DRAWING

NAME

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

TE Connectivity

TERMINAL BLOCK, PCB MOUNT
35 deg. WIRE ENTRY, HIGH CURRENT
W/INTERLOCK, 9.52mm PITCH

A200779

C-796741

SCALE 3:1

SHEET 2 OF 2

REV C