

## MULTI-BEAM | MULTI-BEAM HD

TE Internal #: 2204426-1

Header, Receptacle, Board-to-Board, 23 Position, 2 mm / 6 mm [. 078 in / .236 in] Centerline, MULTI-BEAM HD, Rectangular Power

Connectors

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors











Rectangular Power Connector Type: Header

Connector & Housing Type: Receptacle

Connector System: Board-to-Board

Number of Positions: 23

Centerline (Pitch): 2 mm, 6 mm [ .078 in, .236 in ]

## **Features**

## **Product Type Features**

Rectangular Power Connector Type	Header
Connector & Housing Type	Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

## **Configuration Features**

Number of Positions by Circuit Application	8VP/Power,15/Signal
Number of Positions	23
PCB Mount Orientation	Vertical
Number of Power Positions	8
Number of Signal Positions	15
Number of Rows	5

#### **Electrical Characteristics**

Operating Voltage	60 VDC, 200 VDC



## **Contact Features**

Contact Mating Area Plating Material	Gold Flash over Palladium Nickel
Contact Underplating Material	Nickel
Contact Current Rating (Max)	75 A
Contact Retention Within Housing	Without
Contact Type	Receptacle
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	.076 μm[3 μin]
Termination Features	
Termination Post & Tail Length	3.2 mm
Termination Method to PCB	Through Hole - Press-Fit
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	
Centerline (Pitch)	2 mm, 6 mm[.078 in][.236 in]
Housing Color	Black
Housing Material	High Temperature Thermoplastic
Dimensions	
Row-to-Row Spacing	2 mm[.079 in]
Usage Conditions	
Operating Temperature Range	-40 - 125 °C[-40 - 257 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	

UL Flammability Rating	UL 94V-0
Glow Wire Rating	High Temperature Part - Not Glow Wire

# Packaging Features

Packaging Method	Box & Tray
------------------	------------

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts



Also in the Series | MULTI-BEAM HD





# Customers Also Bought















## **Documents**

## **Product Drawings**

MULTI-BEAM HD VERTICAL REC. 15S+4P+4P

English

## **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2204426-1\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2204426-1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2204426-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Header, Receptacle, Board-to-Board, 23 Position, 2 mm / 6 mm [.078 in / .236 in] Centerline, MULTI-BEAM HD, Rectangular Power Connectors



**Product Specifications** 

**Application Specification** 

English

Agency Approvals

UL

English