

High-precision female headers soldering technique

for □ 0.635 mm and up to 0.85 mm Ø

<p>art. no.</p> <p>BL 5 ...</p>			
<p>art. no.</p> <p>BL 6 ...</p>			
<p>art. no.</p> <p>BL KG 3 ...</p>			
<p>art. no.</p> <p>BL 7 ...</p>			
<p>please indicate:</p>		<p>... no. of contacts</p> <p>one row 1-36</p> <p>two rows 2-72</p> <p>three rows 9-96</p>	
<p>art. no.</p> <p>BL 8 ...</p>			
<p>please indicate:</p>		<p>... no. of contacts</p> <p>two rows 4-72</p>	

contact shell surface: tin-plated

contact spring: gold-plated

BL 8 ...: packing (option) bar magazine (min. 6 contacts)

No capillary action when soldering due to protected contact insert.

V-notches permit breaking! Therefore any required number of contacts is available.

Female headers 2.00 solder

Female headers 2.00 SMD

Technical data

High-precision female headers

→ G 54

→ G 58

→ G 72 - 76

→ G 3 - 5

Male headers 2.00 solder

Male headers 2.54 solder

Male headers 2.54 SMD

→ G 51 - 53

→ G 8

→ G 36 - 40

G 30

A

B

C

D

E

F

G

H

I

K

L

M

N