

Product data sheet

Characteristics

BR900G-FR

APC Back-UPS Pro, 900VA/540W, Tower, 230V, 6x French/Belgian outlets, AVR, LCD, User Replaceable Battery



Overview

| | |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

Main

| | |
|---------------------------|--|
| Main Input Voltage | 230 V |
| Rated power in W | 540 W |
| Rated power in VA | 900 VA |
| Product or component type | Uninterruptible power supply (UPS) |
| Output connection type | 3 French/Belgian 3 French/Belgian surge |
| Cable length | 1.5 M |
| Number of cables | 1 |
| Battery type | Lead-acid battery |

Batteries & Runtime

| | |
|--|---|
| Number of battery filled slots | 0 |
| Number of battery free slots | 0 |
| Battery recharge time | 8 H |
| Number of battery replacement quantity | 1 |
| Battery voltage | 24 V |
| Battery capacity | 7.0 Ah |
| Battery charger power | 20 W rated |
| Battery life | 3...5 Year(S) |
| Battery graph comments | This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v |
| Extended runtime | 0 |

General

| | |
|-------------------------------------|--------------------------|
| Provided equipment | User manual USB cable |
| Number of power module free slots | 0 |
| Number of power module filled slots | 0 |
| Redundant | No |

Physical

| | |
|---------------------|--------------------|
| Colour | Black |
| Height | 25 Cm |
| Width | 10 Cm |
| Depth | 38.2 Cm |
| Net weight | 10.72 Kg |
| Mounting preference | No preference |
| Mounting mode | Not rack-mountable |
| Two post mountable | 0 |
| USB compatible | No |

Input

| | |
|----------------------------|---------------------------------------|
| Network frequency | 50/60 Hz +/- 3 Hz auto-sensing |
| Input voltage limits | 156...300 V adjustable 176...294 V |
| Maximum input current | 8 A |
| Switching current capacity | 10 A |

Output

| | |
|----------------------------------|--|
| Maximum configurable power in W | 540 W |
| Output frequency | 50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised |
| UPS type | Line interactive |
| Wave type | Stepped approximation to a sine wave |
| Bypass type | Built-in bypass |
| Maximum configurable power in VA | 900 VA |
| Transfer time | 8 ms typical : 10 ms maximum |

Conformance

| | |
|-----------------------------|--|
| Product certifications | A-Tick[RETURN]C-Tick[RETURN]CE |
| Marking | GS Mark |
| Standards | EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018 |
| Equipment protection policy | Lifetime : \$150000 |

Environmental

| | |
|---------------------------------------|-------------------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % |
| Operating altitude | 0...9842 ft |
| Ambient air temperature for storage | -15...45 °C |
| Storage Relative Humidity | 0...95 % |
| Storage altitude | 0.000000000...14999.8 M |
| Acoustic level | 45 dBA |

Communications & Management

| | |
|---------------|--|
| Control panel | Multifunction LCD status and control console |
| Alarm | Alarm when on battery : distinctive low battery alarm : overload continuous-tone alarm |

Surge Protection and Filtering

| | |
|----------------------------|-------|
| Surge energy rate | 613 J |
| Let through voltage rating | 330 V |

Packing Units

| | |
|------------------------------|----------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 33.7 Cm |
| Package 1 Width | 22.5 Cm |
| Package 1 Length | 48.7 Cm |
| Package 1 Weight | 11.7 Kg |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 2 |
| Package 2 Height | 35 Cm |
| Package 2 Width | 46 Cm |
| Package 2 Length | 49 Cm |
| Package 2 Weight | 25 Kg |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 24 |
| Package 3 Height | 80 Cm |
| Package 3 Width | 80 Cm |
| Package 3 Length | 120 Cm |
| Package 3 Weight | 312 Kg |
| SCC14 | 10731304279584 |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Optimized Energy Efficiency | Energy efficient product |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 3 years repair or replace |
|----------|---------------------------|

Product Life Status : **Commercialised**