

## PCI Express to 2 PCI & 2 PCIe Expansion Enclosure System - Full Length - TAA

**Product ID:** PEX2PCIE4L



The PEX2PCIE4L PCI/PCI Express Expansion Chassis provides a quick and simple I/O expansion solution to almost any PCI Express (PCIe) enabled system. Adding PCI/PCIe cards to a server or workstation, or providing a platform to swap cards between a mobile and desktop setup is a cost-effective and time-saving solution for maximizing the I/O capabilities of your system.

The external expansion chassis adds two full-length (35cm) PCI slots (32-bit/33MHz), as well as two PCIe x1 (single-lane) slots to a host computer through a single PCI Express connection. Providing total bandwidth up to 250MBps from the PCIe x1 host controller card allows the computer to function as though the expansion chassis cards were connected directly to the motherboard.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Certifications, Reports and Compatibility



### Applications

- Expand an existing systems PCI and PCI Express I/O capabilities
- Add full-length or full-height cards to a small form factor system

- Provide PCI support to systems with only PCIe slots
- Ideal for system testers, and engineers who regularly swap out PCI or PCIe I/O cards

## Features

- Expansion bay providing 2 PCI ports (32-bit/33 MHz), and 2 PCIe single-lane ports (250MBps)
- Self-powered PCI/PCIe expansion system with an on/off button
- Rugged steel construction satisfies demands of industrial and server environments
- Supports both 5V and 3.3V & 5V add-in PCI cards
- Complies with PCI 2.3 and PCIe 1.1 specifications
- Supports advance error reporting including ECRC support
- Support add-in cards with extended length (35cm)

---

### Hardware

Warranty	2 Years
Interface	PCI Express
Bus Type	PCI Express
Card Type	Standard Profile (LP bracket incl.)
Port Style	Integrated on Card
Chipset ID	Texas Instruments - XIO200A Texas Instruments -XIO3130

---

### Performance

Maximum Data Transfer Rate	250 MBps
MTBF	135,012 Hours

---

### Connector(s)

Connector Type(s)	1 - PCI Express x1
External Ports	2 - PCI / PCI-X (Universal 3.3 & 5V, 32-bit) Slot 2 - PCI Express x1 Slot

---

**Software**

OS Compatibility	OS Independent; No additional drivers or software required
------------------	--

---

**Special Notes / Requirements**

Note	This product has a compatibility issue with Silicon Image SATA Controllers on an AMD platform
	The chassis provides up to 5V @ 3A, 3.3V @ 4.5A, or a combined total of 15 Watts

---

**Power**

Power Source	AC Adapter Included
Input Voltage	100 - 240 AC
Output Voltage	12V DC
Output Current	3A
Center Tip Polarity	Positive
Plug Type	M
Power Consumption (In Watts)	36

---

**Environmental**

Operating Temperature	0C to 55C (32F to 131F)
Storage Temperature	-40C to 75C (-40 to 167F)
Humidity	5 to 95% RH

---

**Physical Characteristics**

Color	Black
Material	Steel
Product Length	15.0 in [38.2 cm]
Product Width	5.4 in [13.7 cm]
Product Height	5.6 in [14.3 cm]
Weight of Product	4.3 lb [2.0 kg]

---

**Packaging Information**

Package Quantity	1
Package Length	17.4 in [44.2 cm]
Package Width	8.1 in [20.6 cm]
Package Height	9.4 in [24.0 cm]
Shipping (Package) Weight	7.8 lb [3.5 kg]

---

**What's in the Box**

Included in Package	1 - PCI Expansion box
	1 - PCI Express Card
	1 - 3 ft. DVI-D Cable
	1 - Low Profile Bracket
	1 - Screw Kit
	3 - Power Cord (NA/UK/EU)
	1 - Power Adapter
	1 - Software CD
	1 - Instruction Manual

---

***\*Product appearance and specifications are subject to change without notice.***