

NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

2. MODIFICATIONS: END CAP;

REDUCED DIA. WIRE SEAL


- 3. SPECIFICATIONS:
  - 3.1 CURRENT RATING: 13 AMPS
  - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
  - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
  - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
  - 3.5 MOISTURE RESISTANCE:

IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)

- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: AT04-2P\* RECEPTACLE ( \* = MODIFICATIONS AND COLORS )
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

| <u>/</u> 6\ | CONTACT | SIZE AND RE  | AR SEAL WIF | RE RANGE: |
|-------------|---------|--------------|-------------|-----------|
|             | CONTACT | MINI INISHII | MAY INGLI   | TYPICAI   |


| CONTACT | MIN. INSUL           | MAX. INSUL | TYPICAL                                  |
|---------|----------------------|------------|--|
| SIZE    | O.D.                 | O.D.       | WIRE RANGE                               |
| 16      | 1.35 mm<br>(.053 in) |            | 14 - 20 AWG<br>(2.0-0.5mm <sup>2</sup> ) |



| PART NUMBER CHART |                 |  |  |  |  |
|-------------------|-----------------|--|--|--|--|
| COLOR             | PART NUMBER     |  |  |  |  |
| GREY              | AT06-2S-MM01    |  |  |  |  |
| BLACK             | AT06-2S-MM01BLK |  |  |  |  |
| BLUE              | AT06-2S-MM01BLU |  |  |  |  |
| BROWN             | AT06-2S-MM01BRN |  |  |  |  |
| GREEN             | AT06-2S-MM01GRN |  |  |  |  |
| RED               | AT06-2S-MM01RED |  |  |  |  |
| WHITE             | AT06-2S-MM01WHT |  |  |  |  |
| YELLOW            | AT06-2S-MM01YEL |  |  |  |  |
| ORANGE            | AT06-2S-MM01ORG |  |  |  |  |

|     | REVISIONS |                        |         |       |       |  |  |
|-----|-----------|------------------------|---------|-------|-------|--|--|
| REV | ECO       | DESCRIPTION            | DATE    | BY    | APPR  |  |  |
| A3  | -         | RELEASE NEW DWG FORMAT | 19NOV13 | DRP   |       |  |  |
| A4  | C0540S    | UPDATE                 | 20MAY16 | JONY  | TOMMY |  |  |
| A5  | -         | ADD COLOR OPTION       | 23NOV20 | LOUIE | TOMMY |  |  |

REQUIRES CONTACT RETENTION WEDGE AW2S



STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLORS SHOWN IN PART NUMBER CHART ARE AVAILABLE VIA SPECIAL ORDER.

|  | SEE PART N   | UMBER C   | HART                       |             | REF: DT06-2S-CE                     | 01, DT06-2S-CE03, DT06 | -2S-CE05     |  |  |
|--|--|-----------|----------------------------|-------------|-------------------------------------|------------------------|--------------|--|--|
|  | PART N   | IUMBER    |                            | DESCRIPTION |                                     |                        | ITEM         |  |  |
| QUANTITY   |  |           | MAT                        | ERI         | ALS LI                              | ST                     |              |  |  |
| UNLESS OTHERWISE SPECIFIED  1) All dimensions are in metric(mm). |  | SIGN      | ATURES                     | DATE        | ATE Amphonol                        |                        |              |  |  |
| 2) Tolerances are a<br>1 PL DEC ±0.30                            |  | DRAWN:    | LOUIE                      | 23NOV20     | Amphenol                            |                        |              |  |  |
| 2 PL DEC ±0.15<br>3 PL DEC ±0.08                                 | Angles ±1°   | CHECKED:  | ORION                      | 25NOV20     |                                     | Sine Systems - ww      | w.sineco.com |  |  |
| 3) Note reference = X  |  | ENGINEER: |                            |             | 44724 Morley Drive                  |                        |              |  |  |
| MATERIAL SPECIFICA   | TIONS:   | APPROVAL: | TOMMY                      | 27NOV20     |                                     | Clinton Township, I    | VII 48036    |  |  |
| MATERIAL SPECIFICATIONS.   |  | CUSTOMER: |                            |             | PLUG, 2 SOCKET, AT SERIES, END CAP, |                        |              |  |  |
|  | THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS. |           | REDUCED DIAMETER WIRE SEAL |             |                                     |                        |              |  |  |
| PROCESS SPECIFICATIONS:  NEXT ASSY:                              |  |           | B C-                       | AT06-2S-    | MM01XX                              | ίX                     | A5           |  |  |
|  |  |           | SCALE: NONE                |             | SHEET                               | 1 or                   | 1            |  |  |

AT06-2S-MM01XXX

TITLE PLUG, 2 SOCKET, AT SERIES, END CAP, REDUCED DIA, WIRE SEAL

돐