

1	2	3	4	5	6	7	8																																																														
POGO PIN REAC/ROHS					REV	DESRIPTION	DATE																																																														
					A1	NEW	2018.06.12																																																														
E					<p>otes: Characteristics:</p> <p>A. Material (材料)</p> <ol style="list-style-type: none"> <li>1) Housing:High Plastic Black(UL94V-0)</li> <li>2) Plunger:brass c3604</li> <li>3) Barrel:brass c3604</li> <li>4) Spring:Stainless steel wire.</li> </ol> <p>B. Plating (电镀)</p> <ol style="list-style-type: none"> <li>1) Plunger:Plating Min. 3u' Au over Min. 50u' Ni.</li> <li>2) Barrel:Plating Min. 0u' Au over Min. 50u' Ni.</li> <li>3) Spring:Plating Min. 0u' Au</li> </ol> <p>C. Electrical (电学性能)</p> <ol style="list-style-type: none"> <li>1) Operating voltage: 12V Max.</li> <li>2) Opetating current: 3A Max.</li> <li>3) Contact resistance: 30mohm Max. at working height(Quiescence).</li> </ol> <p>D. Mechanical (机械性能)</p> <ol style="list-style-type: none"> <li>1) Total stroke: 1.10mm.</li> <li>2) Working height: 1.0mm.</li> <li>3) Spring Force:45gf±10gf at working height</li> <li>4) Mechanical life: 10,000 cycle min.</li> <li>5) Don't exceed the Max. allowed compression</li> </ol> <p>E. Environmental (环境性能)</p> <ol style="list-style-type: none"> <li>1) Storage and operating temoperature range: -40°C~+85°C</li> <li>2) Humidity range: 10% RH to 90% RH</li> <li>3) Salt spray: 48H</li> </ol> <p>F. Others (其它)</p> <ol style="list-style-type: none"> <li>1) The dimensions marked * are critical, Should be checked in production</li> <li>2) RoHS compliant product.</li> </ol>																																																																
D																																																																					
C																																																																					
B																																																																					
A					<table border="1"> <tr> <td colspan="4" data-bbox="1366 1173 1702 1220">FIRST VIEW</td> <td colspan="4" data-bbox="1702 1173 2139 1220">TITLE: 2.5PH 180度直脚 PA4.0</td> </tr> <tr> <td colspan="4" data-bbox="1366 1220 1702 1300"> </td> <td colspan="4" data-bbox="1702 1220 2139 1300">           The copyright belongs to samzo parts [China] Co., Ltd. please use the material after samzo parts agree to authorize. The final right of interpretation belongs to samzo parts. WWW.KKK-JP.COM         </td> </tr> <tr> <td colspan="4" data-bbox="1366 1300 1702 1348">GENERAL TOLERANCE</td> <td colspan="4" data-bbox="1702 1300 2139 1348">DWG NO: GZ0254-P001</td> </tr> <tr> <td colspan="4" data-bbox="1366 1348 1702 1396"> <table border="1"> <tr> <td>≥0~2&lt;</td> <td>±0.15</td> </tr> <tr> <td>≥2~5&lt;</td> <td>±0.25</td> </tr> <tr> <td>≥5</td> <td>±0.35</td> </tr> </table> </td> <td colspan="4" data-bbox="1702 1348 2139 1396">PART NO: GZ0254230540</td> </tr> <tr> <td colspan="4" data-bbox="1366 1396 1702 1444">DESIGN WANGUIFA 2018.06.12</td> <td colspan="4" data-bbox="1702 1396 2139 1444">MODEL NO: PR5L4015-2P-C-F</td> </tr> <tr> <td colspan="4" data-bbox="1366 1444 1702 1492">CHECKED ZHENGUILAN 2018.06.12</td> <td colspan="4" data-bbox="1702 1444 2139 1492">NAME: POGO PIN</td> </tr> <tr> <td colspan="4" data-bbox="1366 1492 1702 1524">APPROVED LILIANJIANG 2018.06.14</td> <td colspan="4" data-bbox="1702 1492 2139 1524"></td> </tr> </table>			FIRST VIEW				TITLE: 2.5PH 180度直脚 PA4.0								The copyright belongs to samzo parts [China] Co., Ltd. please use the material after samzo parts agree to authorize. The final right of interpretation belongs to samzo parts. WWW.KKK-JP.COM				GENERAL TOLERANCE				DWG NO: GZ0254-P001				<table border="1"> <tr> <td>≥0~2&lt;</td> <td>±0.15</td> </tr> <tr> <td>≥2~5&lt;</td> <td>±0.25</td> </tr> <tr> <td>≥5</td> <td>±0.35</td> </tr> </table>				≥0~2<	±0.15	≥2~5<	±0.25	≥5	±0.35	PART NO: GZ0254230540				DESIGN WANGUIFA 2018.06.12				MODEL NO: PR5L4015-2P-C-F				CHECKED ZHENGUILAN 2018.06.12				NAME: POGO PIN				APPROVED LILIANJIANG 2018.06.14							
FIRST VIEW				TITLE: 2.5PH 180度直脚 PA4.0																																																																	
				The copyright belongs to samzo parts [China] Co., Ltd. please use the material after samzo parts agree to authorize. The final right of interpretation belongs to samzo parts. WWW.KKK-JP.COM																																																																	
GENERAL TOLERANCE				DWG NO: GZ0254-P001																																																																	
<table border="1"> <tr> <td>≥0~2&lt;</td> <td>±0.15</td> </tr> <tr> <td>≥2~5&lt;</td> <td>±0.25</td> </tr> <tr> <td>≥5</td> <td>±0.35</td> </tr> </table>				≥0~2<	±0.15	≥2~5<	±0.25	≥5	±0.35	PART NO: GZ0254230540																																																											
≥0~2<	±0.15																																																																				
≥2~5<	±0.25																																																																				
≥5	±0.35																																																																				
DESIGN WANGUIFA 2018.06.12				MODEL NO: PR5L4015-2P-C-F																																																																	
CHECKED ZHENGUILAN 2018.06.12				NAME: POGO PIN																																																																	
APPROVED LILIANJIANG 2018.06.14																																																																					
1	2	3	4	5	6	7	8																																																														