

NOTES:

额定电流 Current rating: 0.5A

额定电压 Voltage rating: 50V

耐电压 Withstand voltage: 500V AC/minute

接触电阻 Contact resistance :≤40mΩ

绝缘电阻 Insulation resistance: 100MΩ MIN

工作温度 Working temperature: -25℃ ~ +85℃

盐雾测试 Salt spray test: 24H

触点高低PIN不大于0.05mm.

Part No	Pin	A	B	C	D	E	F
FPC-05F-6PH20	6	7.4	2.50	3.6	3.50	2.50	2.50
FPC-05F-8PH20	8	8.4	3.50	4.6	4.50	3.50	3.50
FPC-05F-10PH20	10	9.4	4.50	5.6	5.50	4.50	4.50
FPC-05F-12PH20	12	10.4	5.50	6.6	6.50	5.50	5.50
FPC-05F-14PH20	14	11.4	6.50	7.6	7.50	6.50	6.50
FPC-05F-16PH20	16	12.4	7.50	8.6	8.50	7.50	7.50
FPC-05F-18PH20	18	13.4	8.50	9.6	9.50	8.50	8.50
FPC-05F-20PH20	20	14.4	9.50	10.6	10.50	9.50	9.50
FPC-05F-22PH20	22	15.4	10.50	11.6	11.50	10.50	10.50
FPC-05F-24PH20	24	16.4	11.50	12.6	12.50	11.50	11.50
FPC-05F-26PH20	26	17.4	12.50	13.6	13.50	12.50	12.50
FPC-05F-28PH20	28	18.4	13.50	14.6	14.50	13.50	13.50
FPC-05F-30PH20	30	19.4	14.50	15.6	15.50	14.50	14.50
FPC-05F-32PH20	32	20.4	15.50	16.6	16.5	15.50	15.50
FPC-05F-34PH20	34	21.4	16.5	17.6	17.5	16.5	16.5
FPC-05F-36PH20	36	22.4	17.5	18.6	18.5	17.5	17.5
FPC-05F-40PH20	40	24.4	18.5	20.6	20.5	18.5	18.5
FPC-05F-50PH20	50	29.4	24.5	25.6	25.5	24.5	24.5

MANUFACTURE DWG		 东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd	
UNLESS OTHERWISE SPECIFIED TOLERANCES			TITLE: FPC 0.5PH H2.0 前翻下接
			PAR FPC-05F-NPH20
DECIMALS:	ANGLES:		DWN
.X:±0.35	.X':±3°		CHKD
.XX:±0.25	.XX':±2°		APVD
.XXX:±0.15			SCALE:1:1
CUSTOMER COPY		SIZE:A4	UNIT:MM
		SHEET:1F1	REV:A

RECOMMENDED FPC/FFC DIMENSION